



Forest Fun Trail

CRP200701

Item no. CRP200701-0901

General Product Information

Dimensions LxWxH	988x616x217 cm
Age group	2+
Play capacity (users)	20
Color options	



Children love to balance, bounce, climb and crawl the Forrest Fun Trail, over and over! Each play link adds new challenges, thrills and skills, all supporting toddlers' can-do attitude: the classic tight rope builds balancing skills for beginners and elevated-level players. The innovative Wave Stepper bounces back gently the toddlers' movements, adding to their

understanding of cause and effect as well as their movement control. Balancing up and down The Curved Pod Balancer the toddlers challenge their spatial awareness and balance. The Hangout Pods are fine to sit and sway on, with a friend. The climbing nets add additional climb and rest points. The varied activities train children's muscles and motor skills, balance

and coordination, which are fundamental for moving confidently and securely in the world. Negotiating turn-taking when passing other children on the trail supports children's social-emotional skills and ability to make friends.




Forest Fun Trail


CRP200701



Ropes of UV-stabilized PES rope strands with inner steel cable reinforcement. The polyester yarn is made of +95% Post-consumer materials and is inductively melted onto each strand to obtain excellent wear and tear resistance.



Corocord 'S' clamps are used as universal connections in Corocord products. 8mm stainless steel rods with rounded edges are pressed around the ropes with a special hydraulic press, making them the ideal connector: safe, durable and vandalism-proof, all while allowing the typical movement of rope play structures.



Corocord smart clamps are carefully designed in every detail to ensure superior flexibility in high quality aluminum material. The smart clamps are attached around the posts with four steel bolts. Not used attachment points are closed with PA caps.

Item no. CRP200701-0901	
Installation Information	
Max. fall height	101 cm
Safety surfacing area	66.6 m ²
Total installation time	16.7
Excavation volume	11.23 m ³
Concrete volume	6.80 m ³
Footing depth (standard)	90 cm
Shipment weight	593 kg
Anchoring options	



The steel surfaces are hot dip galvanised inside and outside with lead free zinc. The galvanisation has excellent corrosion resistance in outside environments and requires low maintenance.



Corocord membranes consist of friction-proof rubberized material of conveyor belt quality with excellent UV resistance. Tested and compliant with REACH requirements for PAH. Embedded is a four-layered armoring made of woven polyester. The armoring and the two surface layers result in a total thickness of 8 mm.




Grey round post decks are supported by hot dipped galvanized steel and made of molded 75% post-consumer PP material with a non-skid pattern and texture surface.

**EN
1176**
compliant

Sustainability Data

CRP200701



Cradle to Gate A1-A3	Total CO ₂ emission	CO ₂ e/kg	Recycled materials
	kg CO ₂ e	kg CO ₂ e/kg	%
CRP200701-0901	1,434.00	3.46	44.10

The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))

Kompan A/S
 C.F. Tietgens Boulevard 32C
 DK-5220 Odense SØ
 Denmark



Verification of CO₂ calculation of: Corocord



Data version no. 2023-10-05

The CO₂ calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Corocord" represented by item no.: COR314011-1101.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

Date: 30. October 2023 | Valid until: 30. October 2025

Verified by:

Julie Marie Vejsgaard Larsen, LCA & EPD Consultant

Verification based on report: Validation of CO₂ calculation of 9 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Julie M. V. Larsen.

Publication date: 30. October 2023

By Bureau Veritas HSE
 www.bureauveritas.dk
 +45 7731 1000



