2-Seat Steel Frame H:2.5m

KSW922



Item no. KSW922-0910		
General Product Information		
Dimensions LxWxH	360x184x255 cm	
Age group	2+	
Play capacity (users)	-	
Colour options		



Portal swings are a modern update on a traditional favourite, constructed from galvanised steel. The swings are available in three heights: 2.0m for preschool, 2.5m and 3.0m for school age playgrounds. This highly modular system makes it possible to offer multi-bay swings with as many additional bays as you wish. Each section can be equipped with standard, toddler, cradle or bird's nest seats. Anti-wrap suspensions are available for both standard and cradle seats.





2-Seat Steel Frame H:2.5m

KSW922



Installation InformationTotal installation time4.7Excavation volume1.12 m³Concrete volume0.00 m³Footing depth (standard)90 cmShipment weight181 kgAnchoring optionsIn-groundWarranty InformationHot dip galvanised steelLifetimeMovable parts2 yearsPost10 yearsSpare parts guaranteed10 years	Item no. KSW922-0910		
Iteration volume1.12 m³Excavation volume1.12 m³Concrete volume0.00 m³Footing depth (standard)90 cmShipment weight181 kgAnchoring optionsIn-groundWarranty InformationHot dip galvanised steelLifetimeMovable parts2 yearsPost10 years	Installation Information		
Concrete volume 0.00 m³ Footing depth (standard) 90 cm Shipment weight 181 kg Anchoring options In-ground Warranty Information Hot dip galvanised steel Lifetime Movable parts 2 years Post 10 years	Total installation time	4.7	
Footing depth (standard)90 cmShipment weight181 kgAnchoring optionsIn-groundWarranty InformationHot dip galvanised steelLifetimeMovable parts2 yearsPost10 years	Excavation volume	1.12 m³	
Shipment weight 181 kg Anchoring options In-ground Warranty Information Hot dip galvanised steel Lifetime Movable parts 2 years Post 10 years	Concrete volume	0.00 m³	
Anchoring options In-ground Warranty Information Hot dip galvanised steel Lifetime Movable parts 2 years Post 10 years	Footing depth (standard)	90 cm	
Warranty InformationHot dip galvanised steelLifetimeMovable parts2 yearsPost10 years	Shipment weight	181 kg	
Hot dip galvanised steelLifetimeMovable parts2 yearsPost10 years	Anchoring options	In-ground 🗸	
Hot dip galvanised steelLifetimeMovable parts2 yearsPost10 years			
Movable parts2 yearsPost10 years	Warranty Information		
Post 10 years	Hot dip galvanised steel	Lifetime	
	Movable parts	2 years	
Spare parts guaranteed 10 years	Post	10 years	
	Spare parts guaranteed	10 years	



Sustainability Data

Cradle to Gate A1-A3

KSW922-0910

KSW922



Kompan A/S C.F. Tietgens Boulevard 32C DK-5220 Odense SØ Denmark



Verification of CO₂ calculation of: Freestanding play equipment



Data version no. 2023-10-05

The CO_2 calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Freestanding play equipment" represented by item no.: KSW92011-0910.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

Date: 30. October 2023 | Valid until: 30. October 2025 Verified by:

maiz

Julie Marie Vejsgaard Larsen, LCA & EPD Consultant

Verification based on report: Validation of CO₂ calculation of 9 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Julie M. V. Larsen.

Publication date: 30. October 2023



The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))

Total CO2

emission

kg CO₂e

415.59

CO2e/kg

kg CO₂e/kg

3.21

Recycled

materials

%

46.86