CRP630201





Item no. CRP630201-0901

General Product Information

Dimensions LxWxH 8'6"x6'9"x4'6" 2 - 12

Age group

Play capacity (users)

Color options









The fun of fundamentals makes children play repeatedly: the Hill Climber invites and supports rappelling up steep hills. The excellent combination of stemming the feet onto the hill, holding tight to the rope, and leaning back, walking upwards is a repeatedly thrilling experience. Apart from being great fun, the combination of movement also provides

great gross motor and muscle training. Hands, arms, and upper body are trained when gripping the perfectly sized rope, legs are trained to walk upwards, and core muscles are put to work when leaning back, tensioning the core.

The motor skill training is intense: the spatial

awareness, the sense of balance, and the coordination come to full use. This stimulates the overall motor confidence of the child and helps train the ability to, e.g., judge distances which is essential in street traffic.









Hill climber rope

Physical: trains cross coordination, balance and muscle strength. Cross coordination also stimulates cross-modal perception, necessary for skills such as reading. Social-Emotional: children cooperate when rappelling together.




CRP630201






Corocord ropes with 19mm diameter or more are special 'Hercules' - type with galvanized sixstranded steel wires. Each strand is tightly wrapped with PES yarn, which is melted onto each individual strand. The ropes are highly wear-and vandalism-resistant and can be replaced at site if needed.



The steel surfaces are hot-dip galvanized inside and outside with lead-free zinc. The galvanization has excellent corrosion resistance in outside environments and requires minimal maintenance.



The Corocord Smart Clamps are carefully designed to ensure superior flexibility in highquality aluminum material. The smart clamps are attached around the post with four steel bolts. Unused attachment points are closed with PA caps.



Installation Information						
Max. fall height		0'0"				
Safety surfacing area		Oft ²				
Total installation time		2.2				
Excavation volume	1.	54yd³				
Concrete volume	0.8	86yd³				
Footing depth (standard)		2'11"				
Shipment weight		69lbs				
Anchoring options	In-ground	•				

Item no. CRP630201-0901

Warranty Information				
Chains	10 Years			
Corocord Rope	10 Years			
Hot dip galvanized steel	Lifetime			
Spare Parts Availability	10 Years			



Through the KOMPAN Variant Team, you can choose between additional 7 rope colors and customize your solution. The assortment is a wide span of colors ranking from elegant and expressive black or a natural, neutral hemp color, to a range of attractive and eye-catching signal colors.



Hill climber ropes are ideal embankment play products, usable on slopes of 20-60° and available in various lengths.

Elevated activities	Accessible elevated activities	Accessible ground level activities	Accessible ground level play types
Present			
Required			

ASTM F1487 compliant **Sustainability Data**

CRP630201



Cradle to Gate A1-A3	Total CO ₂ emission	CO₂e/kg	Recycled materials
	kg CO₂e	kg CO₂e/kg	%
CRP630201-0901	85.92	3.49	45.85

The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))



Kompan A/S

C.F. Tietgens Boulevard 32C DK-5220 Odense SØ Denmark



Verification of CO₂ calculation of: Freestanding play equipment



Data version no. 2023-10-05

The CO_2 calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Freestanding play equipment" represented by item no.: GXY916012-3417.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

Date: 30. October 2023 | Valid until: 30. October 2025 Verified by:

mode

Julie Marie Vejsgaard Larsen, LCA & EPD Consultant

Verification based on report: Validation of CO_2 calculation of 9 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Julie M. V. Larsen.

Publication date: 30. October 2023


By Bureau Veritas HSE
www.bureauveritas.dk
+45 7731 1000

CRP630201



* Max fall height | ** Total height | *** Safety surfacing area

* Max fall height | ** Total height



CRP630201
** 4'-6" / 137cm

Click to see SIDE VIEW