### 3-Seat Frame H:2.5m

KSW903





KOMPAN swings can be configured to adapt individual needs and demands. All A-Frame swings are available in 2.0m and 2.5m height with posts of impregnated pine wood or hot dip galvanized steel. As seats we offer standard swing seat, cradle seat, toddler seat or bird nests with a diameter of ø100cm or 120cm. Further the seats are available with either hot

dip galvanized chains or stainless steel chains and if preferred with antiwrap suspensions. The modular swing system also enable multibay configurations with 2, 3, 4 or more sections.

| Item no. KSW903-0902        |                |  |  |  |
|-----------------------------|----------------|--|--|--|
| General Product Information |                |  |  |  |
| Dimensions LxWxH            | 540x240x274 cm |  |  |  |
| Age group                   | 2+             |  |  |  |
| Play capacity (users)       | -              |  |  |  |
| Colour options              |                |  |  |  |





## 3-Seat Frame H:2.5m

KSW903



| Item no. KSW903-0902     |           |             |  |  |
|--------------------------|-----------|-------------|--|--|
| Installation Information |           |             |  |  |
| Total installation time  |           | 5.9         |  |  |
| Excavation volume        | 1.9       | 95 m³       |  |  |
| Concrete volume          | 0.0       | 00 m³       |  |  |
| Footing depth (standard) | 9         | 0 cm        |  |  |
| Shipment weight          | 17        | 73 kg       |  |  |
| Anchoring options        | Surface   | <b>&gt;</b> |  |  |
|                          | In-ground | ~           |  |  |
| Warranty Information     |           |             |  |  |
| Hot dip galvanised steel | Life      | etime       |  |  |
| Movable parts            | 2 y       | /ears       |  |  |
| Spare parts guaranteed   | 10 չ      | /ears       |  |  |



# **Sustainability Data**

KSW903





| Cradle to Gate A1-A3 | Total CO₂<br>emission | CO₂e/kg    | Recycled materials |
|----------------------|-----------------------|------------|--------------------|
|                      | kg CO₂e               | kg CO₂e/kg | %                  |
| KSW903-0902          | 338.68                | 2.07       | 34.81              |

The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))

#### Kompan A/S

C.F. Tietgens Boulevard 32C DK-5220 Odense SØ Denmark



#### Verification of CO<sub>2</sub> calculation of: Freestanding play equipment



Data version no. 2023-10-05

The  $\mathrm{CO}_2$  calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Freestanding play equipment" represented by item no.: KSW92011-0910.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

Date: 30. October 2023 | Valid until: 30. October 2025 Verified by:

mode

Julie Marie Vejsgaard Larsen, LCA & EPD Consultant

Verification based on report: Validation of  ${\rm CO_2}$  calculation of 9 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Julie M. V. Larsen.

Publication date: 30. October 2023

By Bureau Veritas HSE
www.bureauveritas.dk
+45 7731 1000

