CRP812001





Item no. CRP812001-0404

General Product Information

Dimensions LxWxH 777x739x415 cm

Age group 5+

Play capacity (users) 60

Colour options





Children get a kick from the Sensory Dome: thrills, chills and wonderous optic phenomena in a friendly, fun sensory playscape. The Sensory Dome features a rich variety of novel play activities that intrigue, retain and develop children of all abilities in play. The huge nets are suspended vertically as well as horizontally to cater for climbs that are thrilling and meeting

points for chilling. The age-appropriate training of muscles and motor skills when crawling, climbing and navigating through the net scape of the Dome provide children with important play benefits such as strength, stability and confidence in moving. On ground level, varied nets sway when children climb above, creating playful movement and a sense of unity in

players. The transparency of the Sensory Dome makes it a play unit for intense cooperation, consideration and communication across levels and activities.




CRP812001





Drawing wall

Physical: rollers stimulate fine motor skills and sensory stimulation. Social-Emotional: making patterns from both sides supports social-emotional skills such as cooperation and turn taking. Creative: the rollers' different colors make possible patters and signalmaking which inspires creativity.





Dichroic panels

Physical: hanging and leaning on the ropesuspended panels train muscles, balance and cross-coordination. Social-Emotional: twisting the panels to create colorful shadows encourage turn-taking and cooperation skills. Cognitive: wondering about, understanding and explaining the reasons for the color occurrence support logical thinking skills.







Sensory dome net

Physical: the connected nets make the climbers feel the movements of the other climbers. All muscle groups are trained, as well as cross coordination. Social-Emotional: the climbers' movements affect the other climbers. Room for breaks for many and support cooperation and turn-taking skills. The transparent design enables communication and orientation across the unit.









Hangout pod

Physical: sitting and lying enjoying the swaying movements stimulate the sense of balance. Social-Emotional: meeting, taking a break is invited. Turn-taking supports the skills necessary to learn how to avoid conflicts.



Moiré optic panels



Physical: sitting, hanging and leaning on the

discussing the patterns supports negotiating

understanding and explaining reasons for the

rope suspended panels train balance and

and listening skills, training tolerance and

cross-coordination. Social-Emotional:

empathy. Cognitive: wondering about,

pattern support logical thinking skills.







Physical: the rolling feel adds body pressure when lying and trains the balance when seated. This impacts physical stability. The children can feel the movement of their peers climbing and be part of the play. Social-Emotional: the body pressure of the rolls give a soothing, relaxing feel when lying. Creative: the rollers' two sidedness and colors makes it possible to change the patterns of the rollers, which stimulates creativity.







Dragon scale

Physical: the rubber scales add a fun feel to the seat and stimulates the sense of touch. **Social-Emotional:** great point for a break or meeting with friends.

CRP812001




10 years


10 years

Lifetime 2 years

10 years



Turnable optic panels of two 7mm thick polycarbonate plates with a distance of 40mm. The inside graphic print consist of an inner image layer and outer transparent protection layer. Both PC panel and the water-based lacquer are UV stabilized to prevent fading of the print.



The drawing wall rollers are made of high quality UV stabilized and reinforced nylon (PA). The two colored turn able rollers are assembled to the rope with steel pins and small nylon taps ensures position on the rope.



Hangout pod designed with a welded frame of two steel rings which are hot dip galvanized and powder coated. The membrane consist of friction-proof rubberized material of conveyor belt quality with excellent UV resistance.



Max. fall height 267 cm Safety surfacing area 85.9 m² Total installation time 42.2 Excavation volume 8.73 m³ Concrete volume 4.90 m³

Item no. CRP812001-0404 Installation Information

Footing depth (standard) 38 cm Shipment weight 1,431 kg

Anchoring options In-ground

Warranty Information

Corocord (Hercules)

Hollow PE parts

Galvanised Steel

Spare Parts Guarantee

Membrane

Rope



The stainless steel components are made of high-quality stainless steel in compliance with global playground standards. The steel is glass blasted after manufacturing to ensure a smooth gliding surface.



Designed to allow the typical function of rope play structures to move Corocord 'S' clamps are used as universal connections in Corocord products. 8mm stainless steel rods with rounded edges are pressed around the ropes with a special hydraulic press, making them the ideal connector. Our clamps are safe, durable and vandalism-proof.



Corocord smart clamps are carefully designed in every detail to ensure superior flexibility in high quality aluminum material. The smart clamps are attached around the posts with four steel bolts. Not used attachment points are closed with PA caps.




AS 4685

Sustainability Data

CRP812001





| Cradle to Gate A1-A3 | Total CO₂ emission | CO₂e/kg | Recycled materials |
|----------------------|-----------------------|------------|--------------------|
| | kg CO₂e | kg CO₂e/kg | % |
| CRP812001-0404 | 4,604.68 | 4.02 | 43.26 |

The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))

Kompan A/S

C.F. Tietgens Boulevard 32C DK-5220 Odense SØ Denmark



Verification of CO₂ calculation of: Corocord



Data version no. 2023-10-05

The CO_2 calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Corocord" represented by item no.: $\mathrm{COR314011}$ -1101.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

Date: 30. October 2023 | Valid until: 30. October 2025 Verified by:

made

Julie Marie Vejsgaard Larsen, LCA & EPD Consultant

Verification based on report: Validation of CO_2 calculation of 9 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Julie M. V. Larsen.

Publication date: 30. October 2023

By Bureau Veritas HSE www.bureauveritas.dk +45 7731 1000



CRP812001



* Max fall height | ** Total height | *** Safety surfacing area

* Max fall height | ** Total height

