Moments Sign XL, TexMade™

PCM207





With the KOMPAN signage concept, customizable signs can be created for all kinds of outdoor activity areas. Signs are essential to making relevant and prescribed information available for users in private or public places. For example, signs can provide general or practical information or instructions about using a playground, opening hours, ideal user/age

groups, sponsors, contact information, etc.

The customizable signage concept is flexible in using text, signs, and symbols to communicate a message. Selected products with low carbon emissions are available in GreenLine versions, made mainly from post-consumer ocean waste.

Item no. PCM207-0950

General Product Information

Dimensions LxWxH

3'6"x0'4"x7'1"

Age group

Play capacity (users)

Color options



Moments Sign XL, TexMade™

PCM207





Main posts with hot-dip galvanized steel footing are available in different materials: Pressure impregnated pinewood posts. Pre-galvanized inside and outside with powder-coated top finish steel posts. Lead-free aluminum with color anodized top finish. Greenline TexMade posts of 100% post-consumer recycled PE and textile waste.

High-quality polycarbonate with a thickness of 8mm. The graphic prints are added by a unique multi-layer print process where the inner layer is the image and outer transparent layer functions as protection. Both PC panel and the waterbased lacquer are UV stabilized to prevent fading.



Item no. PCM207-0950

Installation Information

2.2 hours Total installation time

Excavation volume $0.07yd^3$ Concrete volume 0yd3

2'9" Footing depth (standard)

Shipment weight 198lbs

Anchoring options In-ground

Warranty Information

Polycarbonate PC 10 Years

panels

Post 10 Years

Spare Parts Availability 10 Years

Sustainability Data

PCM207





Cradle to Gate A1-A3	Total CO ₂ emission	CO₂e/kg	Recycled materials
	kg CO₂e	kg CO₂e/kg	%
PCM207-0950	98.28	1.53	74.84

The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))

Kompan A/S

C.F. Tietgens Boulevard 32C DK-5220 Odense SØ Denmark



Verification of CO₂ calculation of: Park



Data version no. 2023-10-05

The CO_2 calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Park" represented by item no.: PAR4070-0001.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

Date: 30. October 2023 | Valid until: 30. October 2025 Verified by:

Julie Marie Vejsgaard Larsen, LCA & EPD Consultant

Verification based on report: Validation of CO_2 calculation of 9 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Julie M. V. Larsen.

Publication date: 30. October 2023

