Double Chest Press

FSW244



Item no.	
General Product Information	
Dimensions LxWxH Age group	cm
Play capacity (users) Color options	•••

The Inclusive Double Chest Press is designed to be accessible for people with physical disabilities. On one side there is plenty of space for a wheelchair user to do chest press directly from the wheelchair or to do horizontal row facing opposite direction. The seated side provides low-resistance muscle training without any settings of load or position. The design of the products allows for two people to work out together.



Double Chest Press

FSW244




Item no.	
Installation Information	
Max. fall height	0 cm
Safety surfacing area	0.0 m²
Total installation time	
Excavation volume	
Concrete volume	
Footing depth (standard)	
Shipment weight	
Anchoring options	
Warranty Information	

Sustainability



Kompan A/S C.F. Tietgens Boulevard 32C DK-5220 Odense SØ Denmark







Data version no. 2021-09-27

The CO_2 calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Fitness" represented by item no.: FAZ10100-0900

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

Date: 15. October 2021 | Valid until: 15. October 2023 Validated by:

Bost Octo

Bente Hviid, Senior Consultant

Peter Bendtsen, Senior Consultant

Validation based on report: Validation of CO₂ calculation of 8 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Bente Hviid and Peter Bendtsen.

Publication date: 15. October 2021

By Bureau Veritas HSE www.bureauveritas.dk +45 7731 1000



Cradle to Gate A1-A3

Total CO₂ emission

² C

CO₂e/kg

Recycled

materials

%

kg CO2e kg CO2e/kg

The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))



FSW244

* Max fall height | ** Total height | *** Safety surfacing area

KOMPAN Let's play

9

* Max fall height | ** Total height

Click to see TOP VIEW

Click to see SIDE VIEW

4 / 08/08/2023