





# Sprinter with Roof

PCE105632



|                             |   |
|-----------------------------|---|
| Item no. PCE105632-0903     |   |
| General Product Information |   |
| Dimensions LxWxH            | 525x650x406 cm  |
| Age group                   | 2 - 5   |
| Play capacity (users)       | 16  |
| Colour options              |    |



Wow! The Sprinter will encourage physical as well as social play, the ingredient to helping children and their families to stay and play for longer times. With the many opportunities to climb and to slide, children will develop important physical skills as well as social skills when playing on the Sprinter. Climbing supports cross-coordination, which again


supports the brain's readiness for reading. The open spaces at elevation will also encourage children to socialize. The different options for sliding to the ground adds to the thrill. Sliding develops the child's trunk stability and sense of balance. These are important skills for moving with confidence. The double slide invites social play and inclusive play. Sliding with friends

stimulate cooperation and turn-taking. Children will be delighted by the Sprinter, which encourages healthy outdoor play.



# Sprinter with Roof

PCE105632



## Double slide

**Physical:** sliding develops spatial awareness and a sense of balance. Furthermore, the core muscles are trained when sitting upright going down. **Social-Emotional:** invites socializing, supports parent-child and peer-to-peer play. **Cognitive:** young children train their understanding of space, speed and distances when sliding down quickly.



## Somersault bar

**Physical:** develop balance and core when hanging from knees. Arm, leg and core muscles are developed when climbing up, somersaulting around. Balance and spatial awareness are strengthened. **Social-Emotional:** meeting, socializing and turn-taking when climbing up and down via bar.



## Hammock

**Physical:** coordination and sense of balance when swaying. **Social-Emotional:** meeting, pushing friends gently back and forth, turn-taking. **Cognitive:** for toddlers cause and effect understanding.



## Climbing pole

**Physical:** cross coordination and muscle strength are trained. **Social-Emotional:** turn-taking and cooperation.



## Megaphone

**Social-Emotional:** inspires communication and turn-taking skills. **Cognitive:** distortion of sound evokes curiosity and stimulates an understanding of cause and effect.

# Sprinter with Roof

PCE105632



Panels of 19mm EcoCore™. EcoCore™ is a highly durable, eco friendly material, which is not only recyclable after use, but also consists of material produced from +95% recycled post consumer material from food packing waste.



The ELEMENTS roofs are made of recyclable PE made from 33% post consumer recycled materials with a minimum wall thickness of 5 mm to ensure high durability in all climates around the world. The steel pipes are hot dip galvanised inside and outside for maximum durability.



Sails of commercial 95 high density PE knitted specially for sun-shade structures. The sails are treated with UV stabilizers to ensure a long life-time. The sails are supported by a hot dip galvanised steel frame and tightened by stainless steel devices.



The main posts are made of high quality pregalvanized steel with powder coated top finish. Post tops are closed with caps of UV stabilized nylon (PA6). The grey colored molded decks are made of 75% post-consumer waste PP material with a non-skid pattern and texture surface. All decks are supported by unique designed low-carbon aluminum profiles with multiple attachment options.



The slides are available in either molded PE made from 33% recycled post-consumer materials in different colors or in full AISI304 stainless steel with a thickness of 2mm.



All steel activities has a unique surface treatment of hot dip galvanised base and powder coated top finish to provide durable products with long lifetime for all environments.

|                          |                          |
|--------------------------|--------------------------|
| Item no. PCE105632-0903  |                          |
| Installation Information |                          |
| Max. fall height         | 193 cm                   |
| Safety surfacing area    | 56.6 m²                  |
| Total installation time  | 22.0                     |
| Excavation volume        | 0.63 m³                  |
| Concrete volume          | 0.08 m³                  |
| Footing depth (standard) | 90 cm                    |
| Shipment weight          | 666 kg                   |
| Anchoring options        | In-ground ✓<br>Surface ✓ |
| Warranty Information     |                          |
| EcoCore HDPE             | Lifetime                 |
| Hollow PE parts          | 10 years                 |
| Post                     | 10 years                 |
| PP Decks                 | 10 years                 |
| Spare parts guaranteed   | 10 years                 |

| Elevated activities 5 | Accessible elevated activities | Accessible ground level activities | Accessible ground level play types |
|-----------------------|--------------------------------|------------------------------------|------------------------------------|
| Present               | 5                              | 2                                  | 2                                  |
| Required              | 3                              | 2                                  | 2                                  |

CSA  
Z614  
compliant

# Sustainability Data

PCE105632



| Cradle to Gate A1-A3 | Total CO <sub>2</sub> emission | CO <sub>2</sub> e/kg    | Recycled materials |
|----------------------|--------------------------------|-------------------------|--------------------|
|                      | kg CO <sub>2</sub> e           | kg CO <sub>2</sub> e/kg | %                  |
| PCE105632-0903       | 1,018.70                       | 2.02                    | 56.65              |

The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))

## Verification of CO<sub>2</sub> calculation of: Play systems



Data version no. 2023-10-05

The CO<sub>2</sub> calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Play systems" represented by item no.: PCM200321-0950.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

Date: 30. October 2023 | Valid until: 30. October 2025

Verified by:

Julie Marie Vejsgaard Larsen, LCA & EPD Consultant

Verification based on report: Validation of CO<sub>2</sub> calculation of 9 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Julie M. V. Larsen.

Publication date: 30. October 2023



By Bureau Veritas HSE  
www.bureauveritas.dk  
+45 7731 1000





# Sprinter with Roof

PCE105632

\* Max fall height | \*\* Total height | \*\*\* Safety surfacing area

\* Max fall height | \*\* Total height



PCE105632

[Click to see TOP VIEW](#)

[Click to see SIDE VIEW](#)