Combi Steps

FSW219





As a single item, the step bench is already one of the most versatile pieces of exercise equipment. The KOMPAN Sport & Fitness app covers more than 50 exercises that you can do with it. By putting four in a row you also create a great element for an obstacle course. At each step the exercise becomes heavier and more power is needed to get on top, whether you

step or jump.






Combi Steps

FSW219









A 5 mm hot-dip galvanised carbon steel plate must is moulded inside the SBR to offer optimal stability and optimize the mounting of the step

1011110: 1 OWZ 1900-0900		
Installation Information		
Max. fall height	78 cm	
Safety surfacing area	31.4 m²	
Total installation time	3.9	
Excavation volume	0.51 m³	
Concrete volume	0.34 m³	
Footing depth (standard)	90 cm	
Shipment weight	251 kg	
Anchoring options	In-ground 🗸	
	Surface	~
Warranty Information		
Frame	10 years	
SBR rubber	2 years	
Spare parts guaranteed	10 years	

Item no. FSW21900-0900

The support frame is ø48.3 x 4mm, carbon steel, with a hot-dip galvanised surface according to ISO1461, and a powder coating corrosion class C3 according to ISO12944-2. Lead content for surfaces are below 90ppm.

The surface is produced of recycled SBR (Styrene Butadiene Monomer, Synthetic Rubber) for optimal grip during jumping and step on step off exercises under all weather circumstances.

to the frame.



All KOMPAN fitness products are compliant with the ASTM F3101 & EN16630 Outdoor Fitness Standards. Load tests are performed as a static test by adding dynamic factors as well as safety factors to the specified load of 78kg per user. A product intended for 1 user is loaded with 420kg.



Sustainability Data

Cradle to Gate A1-A3


FSW21900-0900

FSW219



Kompan A/S C.F. Tietgens Boulevard 32C DK-5220 Odense SØ Denmark







Data version no. 2023-10-05

The CO_2 calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Fitness" represented by item no.: FAZ10100-0900.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

Date: 30. October 2023 | Valid until: 30. October 2025 Verified by:

mais

Julie Marie Vejsgaard Larsen, LCA & EPD Consultant

Verification based on report: Validation of CO₂ calculation of 9 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Julie M. V. Larsen.

Publication date: 30. October 2023

By Bureau Veritas HSE www.bureauveritas.dk +45 7731 1000



The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))

Total CO2

emission

kg CO₂e

307.74

CO2e/kg

kg CO₂e/kg

1.81

Recycled


materials

%

65.60



FSW219





361 61 Ø 15⁄0 942 641 (S) FSW21900 *78cm **78cm 50 Ø ***31.4m²



* Max fall height | ** Total height

FSW21900

Click to see TOP VIEW

4 / 06/28/2024