### **Bike High Seat**


FSW247





The Bike offers high exercise value with user-friendly features. It's equipped with a magnetic brake and flywheel system that ensures a smooth cycling experience and adjustable resistance levels. The workload can be easily modified with a conveniently placed handle—starting from a light level of under 50 watts to an intense level that exceeds 500 watts with

rapid pedaling. Its handlebar is designed with multiple positions and a dedicated space for a smartphone, making it versatile for everything from rehabilitation to athletic training. The adjustable seat accommodates users from 160-205 cm.





## **Bike High Seat**

FSW247





The from tube for the frame is made of S235 hot-dip galvanized steel tubing with the following dimensions Ø76,1x3,6mm. and with a powder coating corrosion class C3 according to ISO12944-2.



The resistance unit and all mechanical parts are hidden in the fully closed cabinet which is made from UV-stabilized Polycarbonate (PC). As a result, entrapment is not possible, making it extremely safe to use and providing protection against the elements.



The magnetic resistance system is fully covered and can be adjusted with a rotatable handle in 10 steps. The selector system is intuitive in use, you rotate the handle to select a different amount of resistance.

| Item no. FSW24700-0001   |           |         |  |
|--------------------------|-----------|---------|--|
| Installation Information |           |         |  |
| Max. fall height         |           | 105 cm  |  |
| Safety surfacing area    |           | 11.9 m² |  |
| Total installation time  |           | 2.7     |  |
| Excavation volume        | (         | 0.00 m³ |  |
| Concrete volume          | (         | 0.00 m³ |  |
| Footing depth (standard) |           | 0 cm    |  |
| Shipment weight          |           | 130 kg  |  |
| Anchoring options        | Surface   | ~       |  |
|                          | In-ground | t       |  |



The machine is equipped with a weighted flywheel that ensures that the motion stays fluid and comfortable during use.



Seat is made of injection molded soft PUR with a powder coated steel inlay made from s235 steel. The user can choose between 9 different seat heights, ranging between 845mm and 995mm. The seat allows users with a height of 150cm to 195 cm to comfortably use the bike.



The handlebar on the bike accommodates multiple different hand positions and riding styles. The handlebar is made from tubing with a circumference of ø34mm and a thickness of 3mm.

EN 16630 compliant

## **Sustainability Data**

FSW247





| Cradle to Gate A1-A3 | Total CO <sub>2</sub> emission | CO₂e/kg    | Recycled materials |
|----------------------|--------------------------------|------------|--------------------|
|                      | kg CO₂e                        | kg CO₂e/kg | %                  |
| FSW24700-0001        | 295.46                         | 3.70       | 40.57              |

The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))

#### Kompan A/S

C.F. Tietgens Boulevard 32C DK-5220 Odense SØ Denmark



### Verification of CO<sub>2</sub> calculation of: Fitness



Data version no. 2023-10-05

The  $\mathrm{CO}_2$  calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Fitness" represented by item no.: FAZ10100-0900.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

Date: 30. October 2023 | Valid until: 30. October 2025 Verified by:

Julie Marie Vejsgaard Larsen, LCA & EPD Consultant

 $\mbox{Verification based on report: Validation of $\rm CO_2$ calculation of $\rm 9$ categories of Kompan product line, } \\$ 

version 1.0, prepared by: Bureau Veritas HSE, Denmark: Julie M. V. Larsen.

Publication date: 30. October 2023

By Bureau Veritas HSE www.bureauveritas.dk +45 7731 1000




# **Bike High Seat**






\* Max fall height | \*\* Total height | \*\*\* Safety surfacing area

\* Max fall height | \*\* Total height





Click to see TOP VIEW

Click to see SIDE VIEW