KPL819



ltem no. KPL819-0601		
General Product Information		
Dimensions LxWxH	300x10x30 cm	
Age group	4+	
Play capacity (users)	2	
Color options		



Balancing is always an attractive activity to children. This balancing beam invites children to compete individually or against other children. Through play children train and develop their balance and coordination, but they also use the balancing beam as a nice place to gather.





KPL819





Balance beam

Physical: trains the sense of balance, fundamental for all other motor skills that makes it possible to navigate the world confidently and securely. Social-Emotional: turn-taking skills and negotiation when crossing each other on the beam. Room for a seated rest and exchange.



KPL819



Beams are made of pine wood from sustainable European sources. The wood is pressure impregnated Class 3 with Tanalith E3475 according to EN335 (Equivalent to NTR Class AB). The steel surfaces are hot dip galvanised inside and outside with lead free zinc and with powder coated top-finish. The galvanisation has excellent corrosion resistance in outside environments and requires low maintenance.



Item no. KPL819-0601		
Installation Information		
Max. fall height	3	0 cm
Safety surfacing area	16	.6 m²
Total installation time		1.1
Excavation volume	0.3	30 m³
Concrete volume	0.1	13 m³
Footing depth (standard)	6	0 cm
Shipment weight		27 kg
Anchoring options	In-ground	~
	Surface	~
Warranty Information		
Hot dip galvanised steel	Life	etime
Pinewood	10 y	/ears
Spare parts guaranteed	10 y	/ears



Sustainability Data

Cradle to Gate A1-A3

KPL819-0601

KPL819



Kompan A/S C.F. Tietgens Boulevard 32C DK-5220 Odense SØ Denmark



Verification of CO, calculation of: Freestanding play equipment



Data version no. 2023-10-05

The CO, calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Freestanding play equipment" represented by item no.: GXY916012-3417.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

Date: 30. October 2023 | Valid until: 30. October 2025 Verified by:

maiz

Julie Marie Vejsgaard Larsen, LCA & EPD Consultant

Verification based on report: Validation of CO, calculation of 9 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Julie M. V. Larsen.

Publication date: 30. October 2023



By Bureau Veritas HSE www.bureauveritas.dk +45 7731 1000

BUREAU VERITAS

The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle

Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))

Total CO2

emission

kg CO₂e

26.56

CO2e/kg

kg CO₂e/kg

0.97

Recycled

materials

%

15.54

KPL819



* Max fall height | ** Total height





Click to see TOP VIEW

Click to see SIDE VIEW

