Climbing Structure

NR0818



Item no. NRO818-1001				
General Product Information				
Dimensions LxWxH	14'7"x5'8"x8'4"			
Age group Play capacity (users)	7			
Color options				



The Climbing Structure is a playground favourite with school children. They are immediately attracted to the dense, versatile activity hub. Thanks to the varied climbing opportunities with swaying ropes, rope ladders and stable climbing wall with cleats and climb through hole, all children have a chance of doing something. The openness in design also

invites conversation and social interaction across the Climbing Structure supporting children's social-emotional development. The dare-devils can enjoy a thrilling ride down the bannister bars. With its combination of activities, the Climbing Structure stimulates children's cross-coordination, strength and bone density. All of these abilities are built for life in childhood, so the more they play, the more they gain.



Climbing Structure

NRO818



Climbing grips Physical: dexterity and cross-body coordination, sense of space, all important in navigating the body in space. Pushing, pulling and using fingers, arms, legs and core, strengthen the muscles.





Parkour ropes

Physical: the big rubbery discs are great support for the feet when climbing or crossing. This trains cross coordination, balance and arm and leg muscles. This combination adds to the child's body adeptness and awareness, adding security to movements. Social-Emotional: the seats make a nice destination and meeting point and take cooperation when crossing by others on the way through the module.

KOMP

Let's play



Banister bars

Physical: coordination is supported when going down, as well as arm and core muscles. Landing strengthens bone density, which is built for life in childhood. Social-Emotional: turn-taking and risk-taking.



Rope ladder

Physical: cross coordination is supported when children climb the ladder. The climbing also trains leg and arm muscles. **Social-Emotional:** place for meeting, taking a break and socializing.

Climbing Structure

NRO818





All Organic Robinia products by KOMPAN are made of Robinia wood from sustainable European sources. On request it can be supplied as FSC® Certified (FSC® C004450).



Full colored EPDM rubber seats with smooth surface. The seats is are molded on a hot dip galvanized steel inlay that ensures durable fixation to the rope.



Plywood climbing panel. The climbing panels is made of 21.5mm thick plywood made from alder and pine wood. Both sides are covered by 2 layers of phenolic film with anti slip net pattern. All cutting edges are sealed with paint to ensure long lifetime

Installation Information

Max. fall height		0'0"
Safety surfacing area		0ft²
Total installation time		11.5
Excavation volume	2.7	′9yd³
Concrete volume	0.1	3yd³
Footing depth (standard)		3'3"
Shipment weight	108	89lbs
Anchoring options	In-ground	~

Warranty Information			
EPDM components	2 Years		
Plywood	5 Years		
Robinia Wood	10 Years		
Ropes & nets	10 Years		
Spare Parts Availability	10 Years		



Ropes of UV-stabilized PES rope strands with inner steel cable reinforcement. The polyester yarn is made of +95% Post-consumer materials and is inductively melted onto each strand to obtain excellent wear and tear resistance. The Robinia wood can be supplied as untreated raw wood or painted with a brown colored transparent pigment that maintains the golden wood color of the wood.

Elevated activities 0	Accessible elevated activities	Accessible ground level activities	Accessible ground level play types
Present	0	0	0
Required	0	0	0

Sustainability Data

Cradle to Gate A1-A3

NRO818-1001

NRO818



Kompan A/S C.F. Tietgens Boulevard 32C DK-5220 Odense SØ Denmark



Verification of CO₂ calculation of: Nature play



Data version no. 2023-10-05

The CO_2 calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Nature play" represented by item no.: NR0409-0621.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

Date: 30. October 2023 | Valid until: 30. October 2025 Verified by:

mais

Julie Marie Vejsgaard Larsen, LCA & EPD Consultant

Verification based on report: Validation of CO₂ calculation of 9 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Julie M. V. Larsen.

Publication date: 30. October 2023



B U R E A U V E R I TAS

The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))

Total CO2

emission

kg CO₂e

299.44

CO2e/kg

kg CO₂e/kg

0.68

Recycled

materials

%

7.29



NRO818

* Max fall height | ** Total height | *** Safety surfacing area

* Max fall height | ** Total height

Click to see TOP VIEW

Click to see SIDE VIEW

5 / 10/23/2024

