
Two-mast Spacenet XL

COR32442



Item no. COR324421-1201		
General Product Information		
Dimensions LxWxH	2607x1603x751 cm	
Age group	5+	
Play capacity (users)	112	
Colour options	$\bullet \bullet \bullet \bullet \bullet \bullet \bullet \bullet \bullet$	





This huge classic space net provides any play area with a bouncy, transparent and immensely attractive play event built up around two spectacular high masts. Hours of play spent with friends, family, even parents, or alone will attract users to the playground for many years to come.


Data is subject to change without prior notice.

Two-mast Spacenet XL

COR32442



Transparency Social-Emotional: the transparency makes possible cooperation and communication throughout, all important life-skills for children to learn.







Sturdy, lower rungs

Physical: the stiff bounce of the lower rung supports balance and coordination as well as strengthens bone density when jumping down. Hanging from the arms trains back and upper body muscles, supporting good posture. These are a growing concern for children due to sedentary lifestyles. **Social-Emotional:** great meeting point allowing socializing.

8

Mast

Physical: the slightly swaying mast stimulates children's muscles and motor skills when they hold tight climbing the net. **Social-Emotional:** children develop courage and self-regulation when climbing up high. This positively affects self-confidence.



Bouncy net meshes

Physical: agility, balance and coordination as well as spatial awareness are supported when bouncing, climbing and sitting in the net. Children use muscle strength of arms, legs and core, and build bone density when jumping down. Social-Emotional: the bouncing , swaying net appeals to empathy and cooperation. Cognitive: physical memory, logical thinking, concentration.



Big meshes

Physical: the big meshes allow for climbing and crawling, supporting proprioception, cross coordination and spatial awareness. Climbing here takes muscle strength, pushing and pulling arms to get upwards. **Social-Emotional:** allow more children being seated together, sharing.

Two-mast Spacenet XL

COR32442



Ropes of UV-stabilized PES rope strands with inner steel cable reinforcement. The polyester yarn is made from +95% post-consumer materials and is inductively melted onto each strand. The ropes are highly wear-and vandalism-resistant and can be replaced at site if needed.



Corocord 'S' clamps are used as universal connections in Corocord products. 8mm stainless steel rods with rounded edges are pressed around the ropes with a special hydraulic press, making them the ideal connector: safe, durable and vandalism-proof, all while allowing the typical movement of rope play structures.



The spacenets' main bearing ropes are equipped with an additional safety feature: should the main connections fail, the safety rope prevents collapse of the structure.

Item no. COR324421-1201		
Installation Information		
Max. fall height	215 cm	
Safety surfacing area	285.9 m²	
Total installation time	38.3	
Excavation volume	19.01 m³	
Concrete volume	12.67 m³	
Footing depth (standard)	120 cm	

KON

	12.07 11
Footing depth (standard)	120 cm
Shipment weight	1,505 kg
Anchoring options	In-ground 🗸

Warranty Information		
Corocord rope	10 years	
Membrane	2 years	
S-Clamps	10 years	
Spare parts guaranteed	10 years	
Steel post HDG	Lifetime	



Corocord membranes consist of friction-proof rubberized material of conveyor belt quality with excellent UV resistance. Tested and compliant with REACH requirements for PAH. Embedded is a four-layered armouring made of woven polyester. The armouring and the two surface layers result in a total thickness of 7.5 mm.



In the centre of the net is the mast, made of high quality seamless steel. The structure of the mast as an oscillating support is statically favourable and equalizes the oscillations in the net. The masts are hot dip galvanised as standard, with the design option of additional powder coating.



For installations using rubber surfacing the turnbuckle protectors are to be ordered separately.



Sustainability Data

Cradle to Gate A1-A3

COR324421-1201

COR32442



Kompan A/S C.F. Tietgens Boulevard 32C DK-5220 Odense SØ Denmark



Verification of CO₂ calculation of: Corocord



Data version no. 2023-10-05

The CO_2 calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Corocord" represented by item no.: COR314011-1101.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

Date: 30. October 2023 | Valid until: 30. October 2025 Verified by:

mais

Julie Marie Vejsgaard Larsen, LCA & EPD Consultant

Verification based on report: Validation of CO₂ calculation of 9 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Julie M. V. Larsen.

Publication date: 30. October 2023



The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))

Total CO2

emission

kg CO₂e

4,236.29

CO2e/kg

kg CO₂e/kg

3.10

Recycled

materials

%

55.78





COR32442

* Max fall height | ** Total height | *** Safety surfacing area



* Max fall height | ** Total height





Attention! Foundation anchor blocks exceeds safety zone area. See installation instructions.

Click to see TOP VIEW

Click to see SIDE VIEW

5 / 05/23/2024

Data is subject to change without prior notice.