

# Inclusive Seat, H:3.0m, 2-Chain

SW990206



|                                    |          |
|------------------------------------|----------|
| Item no. SW990206-0107             |          |
| <b>General Product Information</b> |          |
| Dimensions LxWxH                   | 0x0x0 cm |
| Age group                          | 6+       |
| Play capacity (users)              | 1        |
| Color options                      |          |



The rounded shapes of the Inclusive Swing Seat attract children of all ages and abilities. The self-initiated movement, the great ergonomic and the feeling of security while swinging will make children return again and again for more play.

For children who need assistance entering, or support for their seated position, the one-hand

operated harness offers comfortable grips and security. The upright swinging position allows all children eye contact with their care giver and a view of the surroundings while swinging. The thrill of social interaction is ensured by the care giver pushing the child into motion from the front or rear side of the swing seat. When swinging, children train the sensory system of

balance, focal tracking and muscle tonus. But not least, for all children, swinging is one of the most beloved play activities. Participating in the joy of swinging may be the biggest social-emotional thrill of the playground.



# Inclusive Seat, H:3.0m, 2-Chain


SW990206



The inclusive swing seat made of recyclable polyethylene (PE) using 33% post consumer materials. The seat is molded in one piece and equipped with a drain hole to avoid water accumulation. The ergonomic design enables a safe and comfortable seating position.



The Harness is made of molded recyclable polyethylene (PE) made from 33% post consumer materials. The harness utilizes a stainless-steel torsion spring which makes the harness stay in in all position to secure easier entry and exit of users. the harness lock is designed with a one-handed operation slider made from stainless steel.



The front bumper is made with a core of strong polypropylene (PP) with a softer outer layer of thermoplastic rubber (TPE) and the rear bumper of 8mm thick EPDM membrane. The soft, shock absorbent bumpers with nonslip surface makes the swing seat extremely safe to use by caretakers.

Item no. SW990206-0107

### Installation Information

|                          |                     |
|--------------------------|---------------------|
| Max. fall height         | 0 cm                |
| Safety surfacing area    | 0.0 m <sup>2</sup>  |
| Total installation time  | 0.4                 |
| Excavation volume        | 0.00 m <sup>3</sup> |
| Concrete volume          | 0.00 m <sup>3</sup> |
| Footing depth (standard) | 0 cm                |
| Shipment weight          | 37 kg               |
| Anchoring options        |                     |



The seats are available with chains made of either Ø6 hot dip galvanized steel with a surface treatment according to ISO1461 or with Ø6 high-quality stainless-steel chains. Furthermore, the swing seat is available with the unique KOMPAN self-starter function with four chains yolk suspension.



The KOMPAN Inclusive swing seat is available in six different color combinations to ensure it fits into any playground color style. The seats fit all KOMPAN swings with steel crossbeam in height 2,5m and 3,0m.



KOMPAN GreenLine versions are designed with ultimate environmentally friendly materials with lowest possible CO2e emission factor such as EcoCore™ molded PE parts of 33% post-consumer recycled ocean waste.

**EN  
1176**  
compliant

# Sustainability Data

SW990206



| Cradle to Gate A1-A3 | Total CO <sub>2</sub> emission | CO <sub>2</sub> e/kg    | Recycled materials |
|----------------------|--------------------------------|-------------------------|--------------------|
|                      | kg CO <sub>2</sub> e           | kg CO <sub>2</sub> e/kg | %                  |
| <b>SW990206-0107</b> | 64.00                          | 2.30                    | 29.90              |

The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))

**Kompan A/S**  
C.F. Tietgens Boulevard 32C  
DK-5220 Odense SØ  
Denmark



## Verification of CO<sub>2</sub> calculation of: Freestanding play equipment



Data version no. 2023-10-05

The CO<sub>2</sub> calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Freestanding play equipment" represented by item no.: KSW92011-0910.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

**Date: 30. October 2023 | Valid until: 30. October 2025**

Verified by:

Julie Marie Vejsgaard Larsen, LCA & EPD Consultant

Verification based on report: Validation of CO<sub>2</sub> calculation of 9 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Julie M. V. Larsen.

**Publication date: 30. October 2023**

By Bureau Veritas HSE  
www.bureauveritas.dk  
+45 7731 1000



# Inclusive Seat, H:3.0m, 2-Chain

SW990206

\* Max fall height | \*\* Total height | \*\*\* Safety surfacing area

\* Max fall height | \*\* Total height

[Click to see TOP VIEW](#)

[Click to see SIDE VIEW](#)