Hill Climber Rope with EPDM

NR0892



Item no. NRO892-1001				
General Product Information				
Dimensions LxWxH	8'6"x0'7"x4'7"			
Age group	2 - 12			
Play capacity (users)	2			
Color options				



The fun of fundamentals makes children play again and again: the Hill Climber invites and supports rappelling up steep hills. The excellent combination of stemming the feet onto the hill, holding tight to the rope, and leaning back, walking upwards is a repeatedly thrilling experience. Apart from being great fun, the combination of movement also provides great gross motor and muscle training. Hands, arms, and upper body get trained when gripping the perfectly sized rope, legs get trained walking upwards, and core muscles are put to work when leaning back, tensioning the core.

The motor skill training is intense: spatial

awareness, sense of balance, and coordination come to full use. This stimulates the child's overall motor confidence and helps train the ability to judge distances, which is important in street traffic.



Hill Climber Rope with EPDM

NR0892

Hill climber rope with discs

when rappelling together.

Physical: trains cross coordination, balance and muscle strength. Cross coordination also stimulates cross-modal perception, necessary for skills such as reading. Social-Emotional: the discs define sections so that children develop turn-taking and cooperation skills

88





Hill Climber Rope with EPDM



NR0892







All Organic Robinia products by KOMPAN are made of Robinia wood from sustainable European sources. On request it can be supplied as FSC® Certified (FSC® C004450).

ILEIII IIO. NRO092-1001					
Installation Information					
Max. fall height		0'0"			
Safety surfacing area		0ft ²			
Total installation time	2.0 ł	nours			
Excavation volume	1.3	39yd³			
Concrete volume	0.6	69yd³			
Footing depth (standard)		3'3"			
Shipment weight	1	87lbs			
Anchoring options	In-ground	~			

Item no NR0892-1001

Warranty Information					
Chains	10 Years				
Corocord Rope	10 Years				
EPDM components	2 Years				
Robinia Wood	10 Years				
Spare Parts Availability	10 Years				

Corocord ropes with 19mm diameter or more are special 'Hercules' - type with galvanized sixstranded steel wires. Each strand is tightly wrapped with PES yarn, which is melted onto each individual strand. The ropes are highly wear-and vandalism-resistant and can be replaced at site if needed. Through the KOMPAN Variant Team, you can choose between additional 7 rope colors and customize your solution. The assortment is a wide span of colors ranking from elegant and expressive black or a natural, neutral hemp color, to a range of attractive and eye-catching signal colors.



Fully colored EPDM rubber discs with smooth surface. The moulded EPDM surrounds a hot dip galvanized steel core that ensures both the stability of the discs and durable fixation to the rope.



Hill climber ropes are ideal embankment play products, usable on slopes of 20-60° and available in various lengths.

Elevated activities	Accessible elevated activities	Accessible ground level activities	Accessible ground level play types
Present			
Required			

ASTM F1487 compliant

Sustainability Data

Cradle to Gate A1-A3

NRO892-1001

NR0892



Kompan A/S C.F. Tietgens Boulevard 32C DK-5220 Odense SØ Denmark



Verification of CO, calculation of: Nature play



Data version no. 2023-10-05

The CO₂ calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Nature play" represented by item no.: NR0409-0621.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

Date: 30. October 2023 | Valid until: 30. October 2025 Verified by:

mais

Julie Marie Vejsgaard Larsen, LCA & EPD Consultant

Verification based on report: Validation of CO, calculation of 9 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Julie M. V. Larsen.

Publication date: 30. October 2023



+45 7731 1000



The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))

Total CO2

emission

kg CO₂e

25.15

CO2e/kg

kg CO₂e/kg

0.74

Recycled


materials

%

5.94




NR0892






* Max fall height | ** Total height



NRO892 ** 4'-7'' / 139cm



Click to see TOP VIEW

Click to see SIDE VIEW

5 / 06/28/2025