Elephant

M123





Item no. M12373-01P

General Product Information

Dimensions LxWxH 1'4"x2'2"x2'4"

Age group 2 - 5

Play capacity (users) 1



Color options







Rocking on Crazy Nellie is a wildly attractive playground activity that children will return to again and again. Children are able to control the play by moving their bodies to make Crazy Nellie. They will feel delighted to have the elephant respond to their movements. The two sides support the seated position, and the foot and hand holds provide a stable point to stem

feet and hands from, to create the movement. This is not only fun, but is also good for physical and cognitive development. When children begin to learn the connections between their bodies and their movements, they begin to make cognitive connections to a range of body movements and sensations. The horse theme will be attractive to the child's

imagination, and will encourage wonderful physical and imaginative play.



Elephant

M123





Handhold

Physical: the vertical handgrips ensure a firm grip at different heights, necessary for rocking intensely. This trains hand and arm muscles.







Theme

Cognitive: suggests a theme and supports dramatic play, which stimulates language and communication skills.



Foot support

Physical: the possibility of footrest supports intense rocking. Rocking stimulates the senses of balance and space that are fundamental in managing the world securely.







Rocking spring

Physical: response to movement increases spatial awareness and sense of balance. These are fundamental motor skills that help the child's ability to sit still on a chair which takes a good sense of balance. Cognitive: trains the understanding of cause and effect: when I move my body, the spring responds with movement.

Elephant

M123










Panels of 19mm EcoCore™. EcoCore™ is a highly durable, eco friendly material, which is not only recyclable after use, but also consists of a core produced from 100% recycled material.

KOMPAN Springs are made of high quality spring steel according to EN10270. The springs are cleaned by phosphating before they are painted with an epoxy primer and a polyester powder coating as top finish. The springs are fixed by unique anti pinch fittings for maximum safety and long lifetime.

The springs are fixed by unique anti pinch fittings for maximum safety and long lifetime.

Installation Information Max. fall height 1'5" Safety surfacing area 158ft² Total installation time 2.4 hours Excavation volume 0.25yd³ Concrete volume 0yd³ Footing depth (standard) 1'6" Shipment weight 81lbs Anchoring options In-ground ✓ Surface ✓ Warranty Information EcoCore HDPE Lifetime Hot dip galvanized steel Lifetime Spare Parts Availability 10 Years Springs 5 Years	Item no. M12373-01P				
Safety surfacing area 158ft² Total installation time 2.4 hours Excavation volume 0.25yd³ Concrete volume 0yd³ Footing depth (standard) 1'6" Shipment weight 81lbs Anchoring options In-ground Surface ✓ Warranty Information EcoCore HDPE Lifetime Hot dip galvanized steel Spare Parts Availability 10 Years	Installation Information				
Total installation time 2.4 hours Excavation volume 0.25yd³ Concrete volume 0yd³ Footing depth (standard) 1'6" Shipment weight 81lbs Anchoring options In-ground ✓ Surface ✓ Warranty Information EcoCore HDPE Lifetime Hot dip galvanized steel Lifetime Spare Parts Availability 10 Years	Max. fall height		1'5"		
Excavation volume 0.25yd³ Concrete volume 0yd³ Footing depth (standard) 1'6" Shipment weight 81lbs Anchoring options In-ground ✓ Surface ✓ Warranty Information EcoCore HDPE Lifetime Hot dip galvanized steel Lifetime Spare Parts Availability 10 Years	Safety surfacing area		158ft²		
Concrete volume 0yd³ Footing depth (standard) 1'6" Shipment weight 81lbs Anchoring options In-ground Surface ✓ Warranty Information EcoCore HDPE Lifetime Hot dip galvanized steel Lifetime Spare Parts Availability 10 Years	Total installation time	2.4	hours		
Footing depth (standard) 1'6" Shipment weight 81lbs Anchoring options In-ground Surface Warranty Information EcoCore HDPE Lifetime Hot dip galvanized steel Lifetime Spare Parts Availability 10 Years	Excavation volume	0	.25yd³		
Shipment weight 81lbs Anchoring options In-ground Surface Warranty Information EcoCore HDPE Lifetime Hot dip galvanized steel Lifetime Spare Parts Availability 10 Years	Concrete volume		0yd³		
Anchoring options In-ground Surface Warranty Information EcoCore HDPE Lifetime Hot dip galvanized steel Lifetime Spare Parts Availability 10 Years	Footing depth (standard)		1'6"		
Surface Warranty Information EcoCore HDPE Lifetime Hot dip galvanized steel Lifetime Spare Parts Availability 10 Years	Shipment weight		81lbs		
Warranty Information EcoCore HDPE Lifetime Hot dip galvanized steel Lifetime Spare Parts Availability 10 Years	Anchoring options	In-ground	~		
EcoCore HDPE Lifetime Hot dip galvanized steel Lifetime Spare Parts Availability 10 Years		Surface	~		
Hot dip galvanized steel Lifetime Spare Parts Availability 10 Years	Warranty Information				
Spare Parts Availability 10 Years	EcoCore HDPE	Li	fetime		
· · · · · · · · · · · · · · · · · ·	Hot dip galvanized steel	Lifetime			
Springs 5 Years	Spare Parts Availability	10	Years		
	Springs	5	Years		








Handle is made of polypropylene PP with excellent impact strength and usable within a large temperature span.



KOMPAN GreenLine versions are designed with the most environmentally friendly materials with the lowest possible CO2e emission factor such as EcoCoreTM panels of 100% post-consumer recycled ocean waste.





Sustainability Data

M123





Cradle to Gate A1-A3	Total CO ₂ emission	CO₂e/kg	Recycled materials
	kg CO₂e	kg CO₂e/kg	%
M12373-01P	100.50	2.89	55.90

The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))

Kompan A/S

C.F. Tietgens Boulevard 32C DK-5220 Odense SØ Denmark



Verification of CO₂ calculation of: Freestanding play equipment



Data version no. 2023-10-05

The CO_2 calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Freestanding play equipment" represented by item no.: GXY916012-3417.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

Date: 30. October 2023 | Valid until: 30. October 2025 Verified by:

Julie Marie Vejsgaard Larsen, LCA & EPD Consultant

Verification based on report: Validation of CO_2 calculation of 9 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Julie M. V. Larsen.

Publication date: 30. October 2023



M123



* Max fall height | ** Total height | *** Safety surfacing area

* Max fall height | ** Total height

