

FPW216





The wall has three steps to assist the feet and eight handles to help you get over the wall. The scalable wall makes it fun for everyone to play or train together. Everyone will develop muscle strength and bone density when jumping over or even improve their self-esteem if they dare to climb up.

General Product Information

Dimensions LxWxH 120x112x240 cm
Age group 8+
Play capacity (users) 3
Colour options









#### Climbing net

Physical: the inclined net supports the upward climbing movement of the body. The net supports cross-body coordination, which impacts coordination of the right and left part of brain, fundamental for other skills such as the ability to read. The asymmetry of the net challenges the children's climbing.







#### Climbing wall

Physical: develops children's cross coordination, eye-hand coordination, and muscle strength when climbing. Social-Emotional: two-sided climb invites cooperation.

# Wall

### FPW216



10 years



The post is made of Ø101.6 x 2mm, pregalvanised carbon steel and powder coated which is a great protection solution for all climate conditions.



The connectors are made of die-cast aluminium, specially alloyed for the outdoor environments and heavy usage. The screws attaching the connectors are stainless steel and protected by zinc washers.



The wall surface are made of 17.8mm thick high pressure laminate (HPL) panels to ensure optimal strength and durability.

Item no. FPW21600-0900			
Installation Information			
Max. fall height	23	33 cm	
Safety surfacing area	23	3.6 m²	
Total installation time		5.2	
Excavation volume	0.	46 m³	
Concrete volume	0.	19 m³	
Footing depth (standard)	9	90 cm	
Shipment weight	1	75 kg	
Anchoring options	In-ground 🗸		
	Surface	~	
Warranty Information			
Galvanised Steel	Lifetime		
HPL Panel	15 years		
Post	10 years		
Ropes & Nets	10 years		



Corocord 16mm ropes are special 'Hercules'-type with galvanised four-stranded steel wires and a steel wire core. Each strand is tightly wrapped with PES yarn, which is melted onto individual strand. The ropes are hard wearing and vandalism resistant and are easy to replace for any given site.



Spare Parts Guarantee

# **Sustainability Data**

FPW216





C.F. Tietgens Boulevard 32C DK-5220 Odense SØ Denmark



## Verification of CO<sub>2</sub> calculation of: Fitness



Data version no. 2023-10-05

The  $\mathrm{CO}_2$  calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Fitness" represented by item no.: FAZ10100-0900.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

Date: 30. October 2023 | Valid until: 30. October 2025 Verified by:

mode

Julie Marie Vejsgaard Larsen, LCA & EPD Consultant

Verification based on report: Validation of  ${\rm CO_2}$  calculation of 9 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Julie M. V. Larsen.

Publication date: 30. October 2023

By Bureau Veritas HSE
www.bureauveritas.dk
+45 7731 1000



Cradle to Gate A1-A3	Total CO <sub>2</sub> emission	CO₂e/kg Recycled materials	
	kg CO₂e	kg CO₂e/kg	%
FPW21600-0900	254.74	2.35	38.45

The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))









\* Max fall height | \*\* Total height | \*\*\* Safety surfacing area

\* Max fall height | \*\* Total height





Click to see TOP VIEW

Click to see SIDE VIEW