

A-Rahmen Schaukel für 5 Sitze

KSW905-0902

KOMPAN



KOMPAN-Schaukeln können nach individuellen Bedürfnissen und Anforderungen konfiguriert werden. Alle Schaukelrahmen sind in 2,0m und 2,5m Höhe mit Pfosten aus imprägniertem Kiefernholz oder feuerverzinktem Stahl erhältlich. Als Sitze bieten wir Standard-Schaukelsitze, Wiegensitze, Kleinkindsitze oder Vogelnester mit einem Durchmesser von

ø100cm oder 120cm an. Weiterhin sind die Sitze entweder mit feuerverzinkten Ketten oder mit Edelstahlketten und auf Wunsch mit Anti-Überschlag-Aufhängungen erhältlich. Das austauschbare Schaukelsystem ermöglicht auch Mehrfach-Konfigurationen mit 2, 3, 4 oder mehr Sektionen.

Produktnummer KSW905-0902	
Allgemeine Produktinformation	
Masse L x B x H	840x240x274 cm
Empfohlenes Alter	2+
Kapazität (Nutzer)	-
Artikelfarbe	



A-Rahmen Schaukel für 5 Sitze

KSW905-0902



Produktnummer KSW905-0902

Montage-Information

Gesamt-Montagezeit	7,9 stunden
Erforderlicher Erdaushub	3,32 m ³
Betonbedarf	0,00 m ³
Fundamenttiefe (Standard)	85 cm
Versandgewicht	248 kg
Verankerungsoptionen	TV ✓

Garantie-Information

Verzinkter Stahl	Lebenslang
Bewegliche Teile	2 Jahre
Ersatzteilgarantie	10 Jahre





Independent review certificate

Kompan A/S
C. F. Tietgens Blvd. 32C, 5220 Odense SØ

Bureau Veritas hereby attests that the CO₂e-calculations (covering materials, processing, waste and transport) done by Kompan for "Freestanding Play Equipment", meet the requirements set by the listed standard.

Kompan A/S uses a selection of EPDs and emission factors from the Life Cycle Assessment database Ecoinvent 3.11. These values are reported as kg CO₂e, with all other impact categories excluded in line with the scope of ISO 14067:2018. The emission factors cover, material use, manufacturing processes, transport to Kompan, and electricity used during manufacturing. The presented emissions fall under GHG Protocol scope 3 emissions. Scope 1 and 2 are not presented. Scope 3 emissions include emission sources in the upstream value chain of a company, downstream emissions are excluded in this analysis.

Method: ISO 14067:2018 using GHG protocol guidance documents, reported as kg CO₂e.

Object

The verification has been done on the one pager "KSW92011-0910" version: 27-10-2025. The supporting documentation "KOMPAN data_updated emissions factors_2025_V2" and "Emissions factors, EPD's and ecoinvent 3.11_2025" was also reviewed and approved.

Declaration

The verification has been completed as a critical review with a limited assurance. I hereby confirm that nothing has come to the reviewer's attention which would lead to conclude that the study does not give an accurate depiction or isn't completed following method of the CO₂e calculation, the requirements of ISO 14067:2018, and 14071:2024, in the above referenced documentation.

Note: This verification only covers calculation elements according to method described in ISO 14067:2018 and may not be seen as a Life Cycle Assessment according to ISO 14067:2018.

Ref.: Kompan_Verification report 2025, 28-10-2025
Date of certificate: 29-10-2025
Expire date: 29-10-2027

Verified by: Julie Marie Vejsgaard Larsen, Environmental Auditor

Signature: 

Von der Wiege bis zum
Werkstor („cradle to
gate“) (A1–A3)

CO₂-
Emissionen
gesamt

CO₂e pro
kg

Recycelte
Materialien

kg CO₂e

kg CO₂e pro
kg

%

KSW905-0902

839,04

3,59

35,79

Den allgemeinen Rahmen für diese Faktoren bilden die Umweltproduktdeklarationen (EPDs). Mithilfe dieser Grundregeln können die Umweltinformationen über den Lebenszyklus eines Produkts hinweg quantifiziert und Vergleiche zwischen Produkten, die dieselbe Funktion erfüllen, angestellt werden (vgl. ISO, 2006). Diese Struktur wird hier befolgt. Der Ansatz zur Lebenszyklusbewertung wird dabei auf die gesamte Herstellungsphase – vom Rohstoff bis zur Herstellung (A1–A3) – angewendet.