Sign Medium

PAR3003



Item no. PAR3003-0601	
General Product Information	n
Dimensions LxWxH	2'0"x0'2"x3'5"
Age group	
Play capacity (users)	-
Color options	



With the KOMPAN signage concept it's possible to create customisable signs for all kinds of outdoor activity areas. Signs are an important way to make relevant and prescribed information available for the users of private or public areas. E.g. general or practical information or instructions about the use of a playground, opening hours, ideal user/age

groups, sponsors, contact information etc. KOMPAN's customisable signage concept is flexible in the use of text, signs and symbols to communicate a message.



Sign Medium

PAR3003



The steel surfaces are hot dip galvanized inside and outside with lead free zinc. The galvanization has excellent corrosion resistance in outdoor environments and require low maintenance.

High-quality polycarbonate with a thickness of 8mm. The graphic prints are added by a unique multi-layer print process where the inner layer is the image and outer transparent layer functions as protection. Both PC panel and the waterbased lacquer are UV stabilized to prevent fading.

Item no. PAR3003-0601			
Installation Information			
Total installation time		0.6	
Excavation volume	0.	14yd³	
Concrete volume		0yd³	
Footing depth (standard)		2'0"	
Shipment weight		44lbs	
Anchoring options	In-ground 🖌		
	Surface	~	
Warranty Information			
Hot dip galvanized steel	Lif	Lifetime	
Polycarbonate PC panels	10	Years	
Spare Parts Availability	10	Years	



Sustainability Data

Cradle to Gate A1-A3

PAR3003-0601

PAR3003



Kompan A/S C.F. Tietgens Boulevard 32C DK-5220 Odense SØ Denmark



Verification of CO₂ calculation of: Park



Data version no. 2023-10-05

The CO_2 calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Park" represented by item no.: PAR4070-0001.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

Date: 30. October 2023 | Valid until: 30. October 2025 Verified by:

Somo

Julie Marie Vejsgaard Larsen, LCA & EPD Consultant

Verification based on report: Validation of CO₂ calculation of 9 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Julie M. V. Larsen.

Publication date: 30. October 2023



The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))

Total CO2

emission

kg CO₂e

50.57

CO2e/kg

kg CO₂e/kg

3.00

Recycled

materials

%

44.20

Velcome

2-5