M593





Item no. M59300-34

General Product Information

Dimensions LxWxH 32x25x82 cm

Age group 2+

Play capacity (users) 1

Colour options









The Fountain water tap is a fantastic play invitation. With its unique universal design it attracts all children in play again and again. The yellow tap only pours water when pushed, and when the child lets go of it, the water stops running, teaching cause and effect to children. It is put at a height where everyone can reach it. Streaming water holds an eternal attraction

to children, and when merged with sand, the play experience becomes magical. Pushing the tap and feeling the sensation of water streaming will stimulate children's thinking skills and their understanding of cause and effect. Furthermore, the tactile stimulation is intense. Merging water with sand will inspire hours of creative play, shaping and building sand,

getting to know the changing characteristics of sand when it is dry and when it is wet and can be shaped.

















Water tap

Social-Emotional: develops turn-taking and cooperation when helping get water. Opens when pushed with hand, elbow, foot, chin or shoulder. Placed to also be reachable from a seated position. Cognitive: supports cause and effect understanding and logical thinking when figuring out how to push for water and let go for stopping the water stream. Creative: changing the amounts and sequences of the water flow.



M593





The steel surfaces are hot dip galvanised inside and outside with lead free zinc. The galvanisation has excellent corrosion resistance in outside environments and requires low maintenance.



Panels of 19mm EcoCore™. EcoCore™ is a highly durable, eco friendly material, which is not only recyclable after use, but also consists of material produced from +95% recycled post consumer material from food packing waste.



The integrated water tap open for water when pushed and stops when letting go. The water is supplied trough a pipe located inside the post with hose or pipe connection at the bottom of the post. The supply can either a loose hose or a permanent in-ground pluming.

Item no. M59300-34			
Installation Information			
Max. fall height	0 cm		
Safety surfacing area	8.5 m ²		
Total installation time	1.5		
Excavation volume	0.17 m³		
Concrete volume	0.00 m³		
Footing depth (standard)	62 cm		
Shipment weight	22 kg		
Anchoring options	In-ground 🗸		
	Surface <		
Warranty Information			
EcoCore HDPE	Lifetime		
Hot dip galvanised steel	Lifetime		
Movable parts	2 years		
Solid plastic parts	10 years		
Spare parts guaranteed	10 years		



Sustainability Data

M593





Cradle to Gate A1-A3	Total CO ₂ emission	CO₂e/kg	Recycled materials
	kg CO₂e	kg CO₂e/kg	%
M59300-34	51.94	2.73	42.04


The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))

Kompan A/S

C.F. Tietgens Boulevard 32C DK-5220 Odense SØ Denmark



Verification of CO₂ calculation of: Themed play systems



Data version no. 2023-10-05

The CO_2 calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Themed play systems" represented by item no.: MSC641100-3717P.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

Date: 30. October 2023 | Valid until: 30. October 2025 Verified by:

misi

Julie Marie Vejsgaard Larsen, LCA & EPD Consultant

Verification based on report: Validation of ${\rm CO_2}$ calculation of 9 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Julie M. V. Larsen.

Publication date: 30. October 2023


By Bureau Veritas HSE
www.bureauveritas.dk
+45 7731 1000





* Max fall height | ** Total height | *** Safety surfacing area

* Max fall height | ** Total height





Click to see TOP VIEW

Click to see SIDE VIEW