Step, 40cm PU Steel

FAZ30201



Item no. FAZ30201-0900		
General Product Information		
Dimensions LxWxH	61x41x37 cm	
Age group	13+	
Play capacity (users)	1	
Color options		



See KOMPAN Fit app for more







The step is one of the most simple yet highly versatile training tools, so many exercises can be done with it, from simple step ups to plyometric jumps. Regular sessions will provide both cardiovascular and muscular endurance. Incorporating upper and lower body movements will improve balance and agility, and the constant push up onto the step will

increase leg strength.

Step, 40cm PU Steel




FAZ30201



The support frame is ø48.3 x 4mm, carbon steel, with a hot-dip galvanised surface according to ISO1461, and a powder coating corrosion class C3 according to ISO12944-2. Lead content for surfaces are below 90ppm.





A 5 mm hot-dip galvanised carbon steel plate to the frame.

Item no. FAZ30201-0900			
Installation Information			
Max. fall height	;	37 cm	
Safety surfacing area	10.4 m²		
Total installation time		1.6	
Excavation volume	0.13 m³		
Concrete volume	0.	07 m³	
Footing depth (standard)	90 cm		
Shipment weight		76 kg	
Anchoring options	In-ground 🗸		
	Surface	~	



All KOMPAN fitness products are compliant with the ASTM F3101 & EN16630 Outdoor Fitness Standards. Load tests are performed as a static test by adding dynamic factors as well as safety factors to the specified load of 78kg per user. A product intended for 1 user is loaded with 420kg.

The Polyurea Coating, used on all grips, is highly durable against wear and tear, offers isolation and simultaneously gives users an outstanding grip during their workout.

must is moulded inside the SBR to offer optimal stability and optimize the mounting of the step



Sustainability Data

Cradle to Gate A1-A3


FAZ30201-0900

FAZ30201



Kompan A/S C.F. Tietgens Boulevard 32C DK-5220 Odense SØ Denmark







Data version no. 2023-10-05

The CO_2 calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Fitness" represented by item no.: FAZ10100-0900.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

Date: 30. October 2023 | Valid until: 30. October 2025 Verified by:

mais

Julie Marie Vejsgaard Larsen, LCA & EPD Consultant

Verification based on report: Validation of CO₂ calculation of 9 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Julie M. V. Larsen.

Publication date: 30. October 2023

By Bureau Veritas HSE www.bureauveritas.dk +45 7731 1000



The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))

Total CO2

emission

kg CO₂e

107.97

CO2e/kg

kg CO₂e/kg

2.59

Recycled

materials

%

49.84




FAZ30201

* Max fall height | ** Total height | *** Safety surfacing area



361 61 150 150

FAZ30201 *37cm **37cm ***10.4m²



* Max fall height | ** Total height

Click to see TOP VIEW

Click to see SIDE VIEW