Step, 20cm

FPW301



Item no. FPW3	0100-0900
General Product	Information
Dimensions LxWxH	58x39x20 cm
Age group	8+
Play capacity (users)	1
Colour options	






The step is one of the most simple yet highly versatile training tools, so many exercises can be done with it, from simple step ups to plyometric jumps. Regular sessions will provide both cardiovascular and muscular endurance. Incorporating upper and lower body movements will improve balance and agility, and the constant push up onto the step will increase leg strength

Step, 20cm




FPW301





he is ø48.3 x 4mm, carbon dip galvanised surface A 5 mm hot-di must is mould



A 5 mm hot-dip galvanised carbon steel plate must is moulded inside the SBR to offer optimal stability and optimize the mounting of the step to the frame.



The surface is produced of recycled SBR (Styrene Butadiene Monomer, Synthetic Rubber) for optimal grip during jumping and step on step off exercises under all weather circumstances.

Installation InformationMax. fall height20 cmSafety surfacing area10.4 m²Total installation time1.2Excavation volume0.13 m³Concrete volume0.07 m³Easting durth (standard)00 sm	
Safety surfacing area10.4 m²Total installation time1.2Excavation volume0.13 m³Concrete volume0.07 m³	
Total installation time1.2Excavation volume0.13 m³Concrete volume0.07 m³	
Excavation volume0.13 m³Concrete volume0.07 m³	
Concrete volume 0.07 m ³	
Footing depth (standard) 90 cm	
Shipment weight 58 kg	
Anchoring options In-ground	
Surface 🗸	
Warranty Information	
Frame 10 years	
SBR rubber 2 years	
Spare parts guaranteed 10 years	



Sustainability Data

Cradle to Gate A1-A3


FPW30100-0900

FPW301



Kompan A/S C.F. Tietgens Boulevard 32C DK-5220 Odense SØ Denmark







Data version no. 2023-10-05

The CO₂ calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Fitness" represented by item no.: FAZ10100-0900.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

Date: 30. October 2023 | Valid until: 30. October 2025 Verified by:

mais

Julie Marie Vejsgaard Larsen, LCA & EPD Consultant

Verification based on report: Validation of CO, calculation of 9 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Julie M. V. Larsen.

Publication date: 30. October 2023



www.bureauveritas.dk



The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))

Total CO2

emission

kg CO₂e

70.86

CO2e/kg

kg CO₂e/kg

1.77

Recycled


materials

%

66.55



FPW301



* Max fall height | ** Total height

