Seesaw with Seats, 2 persons

NRO12101



Item no. NRO12101-0501		
General Product Information		
Dimensions LxWxH Age group	415x21x117 cm	
Play capacity (users)	2	
Colour options		







The Seesaw is a playground classic. It still attracts players again and again, as it has for generations. The archaic play event is still with us for a reason: the tickling in the stomach when going up high, going down fast is eternally appealing. The Seesaw develops the sense of space and rhythm and leg muscles of children. These are crucial motor skills that help children navigate the world securely, e.g. in the street when estimating time, movement and objects. The social dimension and degree of trust in your peer that is demanded when seesawing, is great training of social-emotional life skills such as turn- taking and cooperation. Empathy is trained as well, as players consider others' limits and limitations. Or as they get inspired to try out things they didn't dare to do before, because other children dare to.



NRO12101





Handhold Physical: the vertical handgrips ensure a firm grip at different heights, necessary for rocking intensely. This trains hand and arm muscles.





Rocking together Social-Emotional: the possibility of rocking two together trains cooperation skills. Consideration of others when rocking.



Rocking movement

Physical: response to movements adds to spatial awareness and sense of balance. These are fundamental motor skills that help the child's ability to sit still on a chair which takes a good sense of balance. Cognitive: trains the understanding of cause and effect: when I move my body, the spring responds with movement.

Seesaw with Seats, 2 persons



NRO12101



All Organic Robinia products by KOMPAN are made of Robinia wood from sustainable European sources. On request it can be supplied as FSC® Certified (FSC® C004450).



The Robinia wood can be supplied as untreated raw wood or painted with a brown coloured transparent pigment that maintains the golden wood colour of the wood.



The steel surfaces are hot dip galvanised inside and outside with lead free zinc. The galvanisation has excellent corrosion resistance in outside environments and requires low maintenance.

Item no. NRO12101-0501			
Installation Information			
Max. fall height		0 cm	
Safety surfacing area	0.0 m²		
Total installation time	3.0		
Excavation volume	0.59 m³		
Concrete volume	0.15 m³		
Footing depth (standard)	70 cm		
Shipment weight	130 kg		
Anchoring options	Surface	~	
	In-ground	~	
Warranty Information			
Hot dip galvanised steel	Lifetime		
Robinia wood	15 years		
Spare parts guaranteed	10 years		

Sustainability Data

Cradle to Gate A1-A3

NRO12101-0501

NRO12101



Kompan A/S C.F. Tietgens Boulevard 32C DK-5220 Odense SØ Denmark



Verification of CO, calculation of: Nature play



Data version no. 2023-10-05

The CO₂ calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Nature play" represented by item no.: NR0409-0621.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

Date: 30. October 2023 | Valid until: 30. October 2025 Verified by:

mais

Julie Marie Vejsgaard Larsen, LCA & EPD Consultant

Verification based on report: Validation of CO, calculation of 9 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Julie M. V. Larsen.

Publication date: 30. October 2023



+45 7731 1000



The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))

Total CO2

emission

kg CO₂e

67.10

CO2e/kg

kg CO₂e/kg

0.61

Recycled

materials

%

33.10



NRO12101

* Max fall height | ** Total height | *** Safety surfacing area

* Max fall height | ** Total height

Click to see TOP VIEW

