Moments Sign M

PCM202



Item no. PCM202-0601			
General Product Information			
Dimensions LxWxH	72x11x110 cm		
Age group			
Play capacity (users)	-		
Colour options	$\bullet \bullet$		

With the KOMPAN signage concept it's possible to create customisable signs for all kinds of outdoor activity areas. Signs are an important way to make relevant and prescribed information available for the users of private or public areas. E.g. general or practical information or instructions about the use of a playground, opening hours, ideal user/age

groups, sponsors, contact information etc. KOMPAN's customisable signage concept is flexible in the use of text, signs and symbols to communicate a message. Selected products are available in GreenLine versions, with low carbon emission, made mainly from postconsumer ocean waste.

Welcome

9



Moments Sign M



PCM202



Main posts with hot dip galvanized steel footing are available in different materials: Pressure impregnated pine wood posts. Pre-galvanized inside and outside with powder coated top finish steel posts. Lead free aluminum with color anodized top finish. Greenline TexMade posts of 95% post-consumer recycled PE and textile waste.

High-quality polycarbonate with a thickness of 8mm. The graphic prints are added by a unique multi-layer print process where the inner layer is the image and outer transparent layer functions as protection. Both PC panel and the waterbased lacquer are UV stabilized to prevent fading.

Item no. PCM202-0601			
Installation Information			
Total installation time		1.5	
Excavation volume	0.2	28 m³	
Concrete volume	0.0	0.00 m³	
Footing depth (standard)	6	60 cm	
Shipment weight	3	31 kg	
Anchoring options	In-ground	~	
	Surface	~	
Warranty Information			
Polycarbonate PC panels	10 y	/ears	
Post	10 y	/ears	
Spare parts guaranteed	10 y	/ears	

Sustainability Data

Cradle to Gate A1-A3

PCM202-0650

PCM202-0601

PCM202



Kompan A/S C.F. Tietgens Boulevard 32C DK-5220 Odense SØ Denmark



Verification of CO, calculation of: Park



Data version no. 2023-10-05

The CO₂ calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Park" represented by item no.: PAR4070-0001.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

Date: 30. October 2023 | Valid until: 30. October 2025 Verified by:

maiz

Julie Marie Vejsgaard Larsen, LCA & EPD Consultant

Verification based on report: Validation of CO, calculation of 9 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Julie M. V. Larsen.

Publication date: 30. October 2023



www.bureauveritas.dk +45 7731 1000





The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))

Total CO2

emission

kg CO₂e

41.97

54.86

CO2e/kg

kg CO₂e/kg

1.53

2.56

Recycled

materials

%

73.84

56.25