Triple Bars

FPW210





Street workout is a physical activity that symbolizes the freedom of movement and encourages socializing. It is a combination of athletics, calisthenics and other sports, and mostly performed in the public space. A Parallel Bar can be found on every street workout area to train the upper body and core stability. This triple parallel bar is 140 cm high, enough to

perform dips with extended legs. The rounded corners make it easy to swing your legs across the Parallel Bars, making it safe to try new tricks without the risk of injuries.

General Product Information

Dimensions LxWxH 197x115x140 cm
Age group 8+
Play capacity (users) 2
Colour options



Triple Bars

FPW210





Post are made of Ø101.6 x 2mm, pregalvanized carbon steel and powder coated, a great protection to all conditions.



The connectors are made of die-cast aluminium, specially alloyed for the outdoor environments and heavy usage. The screws attaching the connectors are stainless steel and protected by zinc washers.



Bars intended as grips during exercises are made of hot-dip galvanised steel ø38mm. A great diameter to support the wrist when doing dips or handstands.

Item no. FPW21000-0900				
Installation Information				
Max. fall height	14	10 cm		
Safety surfacing area	18	8.5 m²		
Total installation time	3.3	hours		
Excavation volume	0.17 m³			
Concrete volume	0.09 m³			
Footing depth (standard)	90 cm			
Shipment weight	1-	46 kg		
Anchoring options	In-ground ✓			
	Surface	•		
Warranty Information				
Connectors	10 years			
Hot dip galvanised steel	Lifetime			
Post	10 years			
Spare parts guaranteed	10	years		



Sustainability Data

FPW210





C.F. Tietgens Boulevard 32C DK-5220 Odense SØ Denmark



Verification of CO₂ calculation of: Fitness



Data version no. 2023-10-05

The CO_2 calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Fitness" represented by item no.: FAZ10100-0900.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

Date: 30. October 2023 | Valid until: 30. October 2025 Verified by:

mais

Julie Marie Vejsgaard Larsen, LCA & EPD Consultant

Verification based on report: Validation of ${\rm CO_2}$ calculation of 9 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Julie M. V. Larsen.

Publication date: 30. October 2023

By Bureau Veritas HSE www.bureauveritas.dk +45 7731 1000





Cradle to Gate A1-A3	Total CO ₂ emission	CO₂e/kg	O₂e/kg Recycled materials	
	kg CO₂e	kg CO₂e/kg	%	
FPW21000-0900	181.73	1.92	67.52	

The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))

Triple Bars





* Max fall height | ** Total height | *** Safety surfacing area

* Max fall height | ** Total height



