# Mauna Kea

PCE211031



Item no. PCE211031-0901				
General Product Information				
Dimensions LxWxH	25'2"x28'2"x10'2"			
Age group	5 - 12			
Play capacity (users)	22			
Color options				





Wow! Endless fun opportunities await in the Mauna Kea! Climbing, sliding, balancing, swaying, and hanging will attract children again and again. The richness of activities supports the development of physical and socialemotional skills in school children. The slides and the Fire-man's Pole help children take turns and negotiate, which supports socialemotional development. The dare-devil fireman's pole is truly thrilling and also supports the child's spatial awareness. The wackle bridge is a challenger. And the Jacob's ladder takes great proprioception and spatial awareness skills to tackle. The monkey bars will help to develop upper body strength, and close the ground children will delight in the hammock. All in all, there's play for hours for all school agers.





PCE211031





## **Overhead ladder**

Physical: develops children's upper body muscles and arm strength, cross coordination and spatial awareness. This is especially important due to sedentary lifestyles and back-pain in children. **Social-Emotional:** chill and socialize on top of the overhead ladder, training cooperation.





### Plank bridge

**Physical:** balancing across the plank develops the vestibular system as well as cross coordination. **Social-Emotional:** passing other children takes co-operation and teaches children turn-taking skills.



### Labyrinth panel

**Social-Emotional:** communication and cooperation exploring the maze with friends. **Cognitive:** stimulates memory when memorizing maze routes.



## Slide

Physical: sliding develops spatial awareness and a sense of balance. Furthermore, the core muscles are trained when sitting upright going down. Social-Emotional: empathy stimulated by turn-taking.



### Binoculars

**Cognitive:** the binoculars set a tangible theme and so spur dramatic play. Dramatic play is great for developing language and communication skills. **Creative:** the binoculars can be turned in all directions. Looking through them gives a new perspective on the world.



Physical: coordination is supported when

going down, as well as arm and core muscles.

Landing strengthens bone density, which is

built for life in early childhood. Social-

Emotional: turn-taking and risk-taking.

Fireman's pole

# 


### Hammock

**Physical:** coordination and sense of balance when swaying. **Social-Emotional:** meeting, pushing friends gently back and forth, turn-taking.

# Mauna Kea







Panels of 19mm EcoCore<sup>™</sup>. EcoCore<sup>™</sup> is a highly durable, eco friendly material, which is not only recyclable after use, but also consists of a core produced from 100% recycled material.



The ELEMENTS roofs are made of recyclable PE made from 33% post consumer recycled materials with a minimum wall thickness of 5 mm to ensure high durability in all climates around the world. The steel pipes are hot dip galvanised inside and outside for maximum durability.



Sails of commercial 95 high density PE knitted specially for sun-shade structures. The sails are treated with UV stabilizers to ensure a long lifetime. The sails are supported by a hot dip galvanized steel frame and tightened by stainless steel devices.

Item no. PCE211031-0901						
Installation Information						
Max. fall height		7'3"				
Safety surfacing area		908ft²				
Total installation time		27.6				
Excavation volume	0.	.89yd³				
Concrete volume	0.08yd³					
Footing depth (standard)	2'11"					
Shipment weight	19	)13lbs				
Anchoring options	In-ground	~				
	Surface	~				
Warranty Information						
EcoCore HDPE	Lit	fetime				
Hollow PE Parts	10	Years				
Post	10	Years				
PP Decks	10	Years				
Spare Parts Availability	10	Years				



The main posts are made of high quality pregalvanized steel with powder coated top finish. Post tops are closed with caps of UV stabilized nylon (PA6). The grey colored molded decks are made of 75% post-consumer waste PP material with a non-skid pattern and texture surface. All decks are supported by unique designed low-carbon aluminum profiles with multiple attachment options.



The slides are available in either molded PE in different colors or in full stainless steel AISI304 t= 2mm.



All steel activities has a unique surface treatment of hot dip galvanized base and powder coated top finish to provide durable products with long lifetime for all environments.

	Elevated activities <b>7</b>	Accessible elevated activities	Accessible ground level activities	Accessible ground level play types
	Present	7	2	2
	Required	4	2	2

**ASTM** F1487 compliant

## **Sustainability Data**

PCE211031




Cradle to Gate A1-A3	e to Gate A1-A3 Total CO <sub>2</sub> emission		Recycled materials
	kg CO₂e	kg CO₂e/kg	%
PCE211031-0901	1,452.33	2.08	59.50

The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))



Kompan A/S C.F. Tietgens Boulevard 32C DK-5220 Odense SØ Denmark







### Data version no. 2023-10-05

The  $CO_2$  calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Play systems" represented by item no.: PCM200321-0950.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

Date: 30. October 2023 | Valid until: 30. October 2025 Verified by:

mais

Julie Marie Vejsgaard Larsen, LCA & EPD Consultant

Verification based on report: Validation of CO<sub>2</sub> calculation of 9 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Julie M. V. Larsen.

Publication date: 30. October 2023






PCE211031

\* Max fall height | \*\* Total height | \*\*\* Safety surfacing area

37'-5" [1140cm]



25'-2" [768cm] 40'-2" [1224cm] 28'-2" [858cm] PCE211031 \* 7'-3" / 221cm \*\* 10'-1" / 309cm \*\*\*908.5ft² / 84.4m² \* Max fall height | \*\* Total height



Click to see TOP VIEW

Click to see SIDE VIEW

5 / 11/14/2024