Dolphin Springer

NR0111



Item no. NRO111-0401	
General Product Information	
Dimensions LxWxH	98x48x69 cm
Age group	3+
Play capacity (users)	1
Colour options	



The Dolphin with its chunky, rocking body attracts toddlers for shorter or longer rides, again and again. Apart from its appealing shape, the Dolphin offers tactile variation with its steel hand hold, rubber tale and fins and smooth, wooden body. Tactile richness is a main motivator, especially in younger children. It supports their understanding of material characteristics such as weight, smoothness, temperature and flexibility. This is important in for instance risk management. The spring ensures hours, years and decades of fun. The soothing, rocking movement of the Dolphin trains the sense of balance and the spatial awareness. These are crucial for body confidence, e.g. in avoiding falling. A good sense of balance is essential for the ability to sit still and concentrate, so this is much more than a mere fun ride.





Data is subject to change without prior notice.

Dolphin Springer

NR0111





Handhold Physical: the vertical handgrips ensure a firm grip at different heights, necessary for rocking intensely. This trains hand and arm muscles.





Theme Cognitive: suggests a theme and supports dramatic play, which stimulates language and communication skills.



Foot support Physical: the possibility of footrest supports intensive rocking. Rocking stimulates the senses of balance and space that are fundamental in managing the world securely.



Rocking spring

Physical: response to movements adds to spatial awareness and sense of balance. These are fundamental motor skills that help the child's ability to sit still on a chair which takes a good sense of balance. Cognitive: trains the understanding of cause and effect: when I move my body, the spring responds with movement.

Dolphin Springer







All Organic oak products by KOMPAN are made of oak wood from sustainable European sources. On request it can be supplied as FSC® Certified (FSC® C004450).



The paint used for coloured components is water based environmentally friendly with excellent UV resistance. The paint is in compliance with EN 71 Part 3.



Handles and footrests are made of high-quality stainless steel and equipped with moulded on PUR handholds and footsteps. The PUR footrests are designed with groves to make the surface slip resistant.

Item 10. NKO 111-040 1		
Installation Information		

Max. fall height	60) cm
Safety surfacing area	7.	8 m²
Total installation time		2.0
Excavation volume	0.1	7 m³
Concrete volume	0.0	0 m³
Footing depth (standard)	42	2 cm
Shipment weight	5	0 kg
Anchoring options	In-ground	~
	Surface	~

Warranty Information

Membrane	2 years
Oak Wood	15 years
Spare parts guaranteed	10 years
Springs	5 years
Stainless steel components	Lifetime



KOMPAN Springs are made of high quality spring steel according to EN10270. The springs are cleaned by phosphating before they are painted with an epoxy primer and a polyester powder coating as top finish. The springs are fixed by unique anti pinch fittings for maximum safety and long lifetime.



Membranes consist of friction-proof rubberized material of conveyor belt quality with excellent UV resistance. Tested and comply with strict PAH requirements. Embedded is a four-layered armouring made of woven polyester to ensure high vandalism resistance. and a second sec

Robinia products are available in three different wood treatment options: Untreated Robinia wood or brown painted with a pigment that maintains the wood colour and coloured version with paint of selected components.



Sustainability Data

Cradle to Gate A1-A3

NRO111-0401

NRO111



Kompan A/S C.F. Tietgens Boulevard 32C DK-5220 Odense SØ Denmark



Verification of CO, calculation of: Nature play



Data version no. 2023-10-05

The CO₂ calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Nature play" represented by item no.: NR0409-0621.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

Date: 30. October 2023 | Valid until: 30. October 2025 Verified by:

sund

Julie Marie Vejsgaard Larsen, LCA & EPD Consultant

Verification based on report: Validation of CO, calculation of 9 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Julie M. V. Larsen.

Publication date: 30. October 2023



www.bureauveritas.dk



The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))

Total CO2

emission

kg CO₂e

69.96

CO2e/kg

kg CO₂e/kg

1.79

Recycled

materials

%

24.83



NR0111

* Max fall height | ** Total height | *** Safety surfacing area

KOMPAN Let's play

* Max fall height | ** Total height



NRO111 *60cm **69cm ***7.8m²



NR0111

Click to see TOP VIEW

Click to see SIDE VIEW

5 / 10/28/2024

Data is subject to change without prior notice.