
Carousel with Bars

KPL115



Item no. KPL115-0501		
General Product Information		
Dimensions LxWxH	155x155x81 cm	
Age group	4+	
Play capacity (users)	10	
Colour options		



Play with a true purpose! The red spinning carousel attracts children and adults alike. With its seating platform height and three handholds, many possible body positions are supported, making this a play champion again and again. The choice of body positions also supports users with various physical disabilities. Pushing or Pulling the carousel into motion from the outside, children take turns spinning and being spun. These movements train leg and arm muscles as well as coordination. Spinning, apart from being a stomach tickling joy, trains the vestibular system and the whole sense of balance. this is fundamental for children's ability to move around the world safely. It's fundamental for walking, running and even being able to sit still and concentrate. So the fun of carousel spinning serves a true purpose.



Data is subject to change without prior notice.

Carousel with Bars

KPL115





Handrails and side poles Physical: pushing or pulling the carousel strengthens arm and leg muscles. Social-Emotional: pushing and pulling others facilitates cooperation and empathy: when to stop, how to take turns etc.





0

Physical: the rotation develops the sense of balance and space, children use their muscle strength and strengthen their cardio. Social-Emotional: listening and negotiating how slow or fast to go, children develop empathy and cooperation skills.



Flat platform


Physical: enables varied body positions e.g. lying, sitting, standing when spinning. **Social-Emotional:** spaciousness invites bigger groups of children playing together.

Carousel with Bars




Lifetime 10 years

KPL115







The steel surfaces are hot-dip galvanised inside and outside with lead free zinc and with powder coated top-finish. The galvanisation has excellent corrosion resistance in outside environments and requires low maintenance. A heavy-duty engineered bearing system with two single row deep groove high-quality ball bearings with rubber seals. The fully closed bearing construction is lifetime lubricated and located above ground. Deck plate of 3mm thick, high-quality aluminium with 2mm texture pattern. This aluminium plate maintains safety requirements and requires low maintenance.

Item no. KPL115-0501		
Installation Information		
Max. fall height	100 cm	
Safety surfacing area	24.2 m²	
Total installation time	2.4 hours	
Excavation volume	0.45 m³	
Concrete volume	0.40 m³	
Footing depth (standard)	80 cm	
Shipment weight	148 kg	
Anchoring options	In-ground 🗸	
Warranty Information		
Aluminium Deck	15 years	
Bearing Construction	5 years	



Galvanised Steel

Spare Parts Guarantee

Sustainability Data

Cradle to Gate A1-A3

KPL115



Kompan A/S C.F. Tietgens Boulevard 32C DK-5220 Odense SØ Denmark



Verification of CO, calculation of: Freestanding play equipment



Data version no. 2023-10-05

The CO, calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Freestanding play equipment" represented by item no.: GXY916012-3417.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

Date: 30. October 2023 | Valid until: 30. October 2025 Verified by:

mais

Julie Marie Vejsgaard Larsen, LCA & EPD Consultant

Verification based on report: Validation of CO, calculation of 9 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Julie M. V. Larsen.

Publication date: 30. October 2023



By Bureau Veritas HSE www.bureauveritas.dk +45 7731 1000

emission materials % kg CO₂e kg CO₂e/kg KPL115-0501 430.54 3.59 43.94

Total CO2


CO2e/kg

Recycled

The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))




KPL115



555



> KPL115 *100cm **81cm ***24.2m²



* Max fall height | ** Total height

KPL115

Click to see TOP VIEW

Click to see SIDE VIEW

5 / 05/12/2025