

Angled Triple Tower

PCM301232



Item no. PCM301232-0906

General Product Information

| | |
|-----------------------|---|
| Dimensions LxWxH | 23'11"x14'10"x9'2" |
| Age group | 2 - 5 |
| Play capacity (users) | 35 |
| Color options |    |



This fantastic play structure will inspire young children to play again and again, stimulating their physical, social and thinking skills. Their muscle and motor skills come in full use, climbing to the top and sliding or gliding in a rotating movement to the ground. The bubble window in the tunnel bridge distorts voices when spoken into, evoking a sense of wonder

and training logical thinking. Sliding down the slide or curly climber to the ground supports posture and balance, all important skills for young children, and great fun! Under deck, a wealth of manipulative play panels stimulate explorative and dramatic play. The panels support logical thinking skills and cooperation.

Angled Triple Tower


PCM301232



Panels of 19mm EcoCore™. EcoCore™ is a highly durable, eco friendly material, which is not only recyclable after use, but also consists of a core produced from 100% recycled material.




All decks are supported by uniquely designed low-carbon aluminum profiles with multiple attachment options. The grey-colored molded decks are made of 75% post-consumer ocean waste PP material with a non-skid pattern and texture surface.



Main posts with hot-dip galvanized steel footing are available in different materials: Pressure impregnated pinewood posts. Pre-galvanized inside and outside with powder-coated top finish steel posts. Lead-free aluminum with color anodized top finish. Greenline TexMade posts of 100% post-consumer recycled PE and textile waste.


| | |
|--------------------------|--------------------------|
| Item no. PCM301232-0906 | |
| Installation Information | |
| Max. fall height | 6'8" |
| Safety surfacing area | 775ft² |
| Total installation time | 32.4 |
| Excavation volume | 1.41yd³ |
| Concrete volume | 0.05yd³ |
| Footing depth (standard) | 2'11" |
| Shipment weight | 2552lbs |
| Anchoring options | Surface ✓ In-ground ✓ |
| Warranty Information | |
| EcoCore HDPE | Lifetime |
| Post | 10 Years |
| PP Decks | 10 Years |
| Ropes & nets | 10 Years |
| Spare Parts Availability | 10 Years |



Ropes are made of UV-stabilized PES rope strands with inner steel cable reinforcement. The polyester wrapping is inductively melted onto each strand to ensure excellent wear and tear resistance.



Wood version of FSC®-certified (FSC®C004450) pine wood with pressure impregnated base treatment and brown painted top finish. Vertical boards and top ends protected by a unique aluminum profile for high outdoor durability.



Shade sails of commercial 95 high density PE knitted specially for sunshade structures. The sails are treated with UV stabilizers to ensure a long lifetime. The sails are supported by a hot dip galvanized steel frame. Closed sail equipped with an easy take down system.

| Elevated activities | Accessible elevated activities | Accessible ground level activities | Accessible ground level play types |
|---------------------|--------------------------------|------------------------------------|------------------------------------|
| Present | | | |
| Required | | | |

Sustainability Data

PCM301232



| Cradle to Gate A1-A3 | Total CO ₂ emission | CO ₂ e/kg | Recycled materials |
|----------------------|--------------------------------|-------------------------|--------------------|
| | kg CO ₂ e | kg CO ₂ e/kg | % |
| PCM301232-0950 | 1,359.03 | 1.47 | 69.80 |
| PCM301232-0906 | 1,573.43 | 1.74 | 36.27 |

The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))

Kompan A/S

C.F. Tietgens Boulevard 32C
DK-5220 Odense SØ
Denmark



Verification of CO₂ calculation of: Play systems



Data version no. 2023-10-05

The CO₂ calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Play systems" represented by item no.: PCM200321-0950.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

Date: 30. October 2023 | Valid until: 30. October 2025

Verified by:

Julie Marie Vejsgaard Larsen, LCA & EPD Consultant

Verification based on report: Validation of CO₂ calculation of 9 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Julie M. V. Larsen.

Publication date: 30. October 2023

By Bureau Veritas HSE
www.bureauveritas.dk
+45 7731 1000





Angled Triple Tower

PCM301232

* Max fall height | ** Total height | *** Safety surfacing area

* Max fall height | ** Total height



[Click to see TOP VIEW](#)

[Click to see SIDE VIEW](#)