
CRP250201





General Product Information

Dimensions LxWxH 32'1"x3'2"x13'5"

Age group 5 - 12

Play capacity (users) 10

Color options



The Bamboo Trail is a great, versatile play invitation in any playground. Its immense appeal will attract children again and again, to try out the tight, bouncy ropes and the varied climbing options. Many children can play at once on the Bamboo trail thanks to the transparent design. This allows for children to see one another, interact and communicate

through the piece. The Climbing Wall can be used from both sides, supporting cooperative play. The challenging Zig-Zag Slider offers rich training of coordination and muscles, and a firm surface in the bouncy surroundings. The trail sways and bounces back the child's movements, adding an element of thrill and concentration to every step. Climbing here is

great fun and may pave the way to friendships for life.



CRP250201





Zig-zag slider Physical: muscle strength, balance and coordination when climbing up and down, holding tight.





Climbing wall

Physical: climbing here develops cross coordination, which supports cross-modal perception, necessary for other skills such as reading.



Swaying seesaw

Physical: the Swaying Seesaw is a challenging training of balance, spatial awareness, and timing: to bounce each other up and down in this link is a balance quest that takes handholds, hence the supportive ropes. The skills trained here are fundamental for navigating traffic safely. Social-Emotional: passing others on the bridge intensely trains cooperation and communication skills.

CRP250201



6'1"

558ft²

7.48yd3

4.45yd3

2'11'

849lbs

11.0 hours



Ropes are made of UV-stabilized PES rope strands with inner steel cable reinforcement. The polyester wrapping is inductively melted onto each strand to ensure excellent wear and tear resistance.



Colored steel components have a base of hot dip galvanization and a powder coated top finish. This provides an ultimate corrosion resistance in all climates around the world. Other steel surfaces are hot dip galvanized inside and outside with lead free zinc.



The Corocord Smart Clamps are carefully designed to ensure superior flexibility in high-quality aluminum material. The smart clamps are attached around the post with four steel bolts. Unused attachment points are closed with PA caps.



Shipment weight

Anchoring options


Surface
In-ground

Warranty Information

Aluminum clamps
Hot dip galvanized steel
Painted toplayer
Ropes & nets
Spare Parts Availability

Surface
In-ground


Lifetime
10 Years
10 Years
10 Years



Panels of 19mm EcoCore™. EcoCore™ is a highly durable, eco friendly material, which is not only recyclable after use, but also consists of a core produced from 100% recycled material.



Rocking tube is made of medium density PE with excellent impact strength and usable within a large temperature span. Hollow plastic components are made of 100% recyclable PE made from 33% post-consumer materials. Molded in one piece with minimum 5mm wall thickness. The longitudinal grooves provides a slip resistant surface for safe play.



The stainless steel components are made of high quality stainless steel in compliance with global playground standards. The steel is glass blasted after manufacturing to ensure a smooth gliding surface.


Elevated activities 0	Accessible elevated activities	Accessible ground level activities	Accessible ground level play types
Present	0	1	1
Required	0	1	1

ASTM F1487 compliant

Sustainability Data

CRP250201





Cradle to Gate A1-A3	Total CO₂ emission	CO₂e/kg	Recycled materials
	kg CO₂e	kg CO₂e/kg	%
CRP250201-0901	1,080.25	3.35	44.95


The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))

Kompan A/S

C.F. Tietgens Boulevard 32C DK-5220 Odense SØ Denmark



Verification of CO₂ calculation of: Corocord



Data version no. 2023-10-05

The CO_2 calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Corocord" represented by item no.: $\mathrm{COR314011}$ -1101.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

Date: 30. October 2023 | Valid until: 30. October 2025 Verified by:

mode

Julie Marie Vejsgaard Larsen, LCA & EPD Consultant

Verification based on report: Validation of CO_2 calculation of 9 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Julie M. V. Larsen.

Publication date: 30. October 2023

By Bureau Veritas HSE
www.bureauveritas.dk
+45 7731 1000





CRP250201



* Max fall height | ** Total height | *** Safety surfacing area

* Max fall height | ** Total height





Click to see TOP VIEW

Click to see SIDE VIEW