Agora Stool

PAR4060





The AGORA STOOL is a part of the award winning funiture line from KOMPAN. AGORA is developed according to the latest inclusive design principles for outdoor furnishings without compromising on design qualities. KOMPAN truly believes in making public spaces more attractive and accessible for all. AGORA offers a high level of flexibility when it

comes to anchoring, color and material options in order to inspire architectural creativity and to fit the site specific requirements for individual customer projects. AGORA comes in durable and robust designs, and is manufactured in low maintenance materials to ensure long-lasting outdoor solutions with the lowest possible total cost of ownership.





Agora Stool

PAR4060





Boards are made of ash wood from sustainable European sources. The ash wood is thermo treated according to CEN/TS 15679, durability class 2 according EN350-2.



Bench is made of pine wood post pressure impregnated class AB with Tanalith E3475 according to EN335.



The steel surfaces are hot dip galvanized inside and outside with lead free zinc. The galvanization has excellent corrosion resistance in outdoor environments and require low maintenance. Painted steel parts are hot dip galvanized before powder coating.

Item no. PAR4060-0621			
Installation Information			
Total installation time		0.2	
Excavation volume	0.1	0.13yd³	
Concrete volume	0.0	0.08yd³	
Footing depth (standard)		2'0"	
Shipment weight	2	27lbs	
Anchoring options	Surface	>	
	In-ground	~	
Warranty Information			
Ashwood	10 Y	10 Years	
Hot dip galvanized steel	Life	Lifetime	
Painted toplayer	10 Y	10 Years	
Pinewood	10 Y	10 Years	
Spare Parts Availability	10 Y	10 Years	



Powder coated top finish on top of galvanization is processed in two steps: Light grinding and clean sweeping, powder coating - thickness 70-120 μm .



The Agora assortment is available in 2 wood types and 9 different frame colors to match the selected color scheme of the play, sport or fitness site.



KOMPAN outdoor furniture is available for surface and in-ground installation. Surface installation involves anchoring to the base layer, and in-ground installation is direct in-ground or additional hot-dip galvanized steel brackets.



Sustainability Data

PAR4060






C.F. Tietgens Boulevard 32C DK-5220 Odense SØ Denmark







Data version no. 2023-10-05

The $\mathrm{CO_2}$ calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Park" represented by item no.: PAR4070-0001.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

Date: 30. October 2023 | Valid until: 30. October 2025 Verified by:


misi

Julie Marie Vejsgaard Larsen, LCA & EPD Consultant

Verification based on report: Validation of CO_2 calculation of 9 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Julie M. V. Larsen.

Publication date: 30. October 2023





The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))