MUSA, 66 x 128, WPC, 3 ft Walls

FRE600403



Item no. FRE600403-0901				
General Product Information				
Dimensions LxWxH	127'4"x65'5"x12'1"			
Age group	3+			
Play capacity (users)	-			
Color options	$\bullet \bullet $			





Wood Plastic Composite (WPC) has the same texture and looks as wood, is maintenance-free and environmentally friendly. WPC fits perfectly into a natural environment. The fully flat inside gives the best bounce experience when playing. The flat wall becomes a part of the game and adds a new dimension to it, a dimension that can challenge and develop players' tactical vision of the game. The 9'10" x 6'7" Multi Goal follows the goal size of FIFA Futsal and IHF Handball regulations. The basketball hoop is placed at the official NBA height of 10 feet, and has the official NBA size of 18 inches in diameter.

MUSA, 66 x 128, WPC, 3 ft Walls



FRE600403



The Wood Plastic Composite panels are made of 100% recycled fibre/wood powder and High Density Poly Ethylene (HDPE). With the dimensions of 860 x 110 x 30mm the boards are extremely strong.



The Panna Goals are 118 x 68cm and the

highlight the target.

distance between the vertical ø21.3mm tubes is


The goal is framed with coloured HDPE strips to

68mm, small enough to keep all balls in play.



The hinges on the entrance gate are 16mm and made of Stainless Steel, the handle can be accessed from both inside and outside of the pitch but is constructed in such a way that it remains fully flat on the inside of the MUGA.

Item no. FRE600403-0901				
Installation Information				
Max. fall height		0'0"		
Safety surfacing area		0ft ²		
Total installation time		97.2		
Excavation volume	5.	58yd³		
Concrete volume	4	.3yd³		
Footing depth (standard)		2'9"		
Shipment weight	120	95lbs		
Anchoring options	In-ground	~		
	Surface	~		
Warranty Information				
EcoCore HDPE	Lif	etime		
HDG post	Lif	etime		
Spare Parts Availability	10 `	Years		



Each panel has 4 Thermoplastic Vulcanizates plugs connecting the panels to the posts. The plugs reduce the vibration and therefore reduce the noise level. The plugs will also simplify installation as the come with pre-assembled nuts.



The posts are made of 80 x 80 x 3mm profile with horizontally, 6mm welded flanges. This will enable an easy installation and strong construction. The low-density polyethylene post caps are attached with blind rivets.



The WPC boards are attached to 70 x 45 x 3mm welded flanges with stainless steel M8 bolts, nuts and washers. These connections are not visible from the inside and create a strong and safe connection.

Sustainability Data

FRE600403



Cradle to Gate A1-A3	Total CO₂ emission	CO₂e/kg	Recycled materials
	kg CO₂e	kg CO₂e/kg	%
FRE600403-0901	10,468.14	1.86	58.97

The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))



Kompan A/S C.F. Tietgens Boulevard 32C DK-5220 Odense SØ Denmark



Verification of CO₂ calculation of: Sport



Data version no. 2023-10-05

The CO_2 calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Sport" represented by item no.: FRE600202-0901.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

Date: 30. October 2023 | Valid until: 30. October 2025 Verified by:

mais

Julie Marie Vejsgaard Larsen, LCA & EPD Consultant

Verification based on report: Validation of CO₂ calculation of 9 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Julie M. V. Larsen.

Publication date: 30. October 2023



By Bureau Veritas HSE

www.bureauveritas.dk


+45 7731 1000



FRE600403

* Max fall height | ** Total height | *** Safety surfacing area

* Max fall height | ** Total height





Click to see TOP VIEW

