Stepping Pod, 1 ft

M87402



| Item no. M87402-3617 | | | | |
|-----------------------------|------------------|--|--|--|
| General Product Information | | | | |
| Dimensions LxWxH | 0'11"x0'11"x1'0" | | | |
| Age group | 2 - 12 | | | |
| Play capacity (users) | 1 | | | |
| Color options | \bullet | | | |





The Stepping Pod, 1FT, appeals to childrento play simple yet thrilling games like the Ground is Lava. Placing more Stepping Pods in various heights adds to attraction, inviting jumping or balancing from one to the next. As an individual Stepping Pod, it can function as a sturdy seat and invite a break from play. The Stepping Pod invites less confident balancing acrobats also, thanks to its sturdy rubber surface. When jumping up on and down from the Stepping Pod, children train their sense of balance. Balance is fundamental in confidently managing the body in its surroundings. This is important for instance when navigating street traffic safely. When jumping down, children additionally build bone density by engaging in weight bearing activity on a hard surface.

Stepping Pod, 1 ft

M87402







Sturdy rubber surface Physical: makes for a skid-resistant surface for jumping up and down, training muscle and motor skills and building bone density.



Stepping pod

Physical: young children learn how to balance and to alternate feet. These are important for the proprioceptive and vestibular systems that help children navigate the world securely. Jumping down builds bone density and muscles.

Stepping Pod, 1 ft

M87402



| ltem no. M87402-3617 | | | | | | |
|--------------------------|--------------------|-------|--|--|--|--|
| Installation Information | | | | | | |
| Max. fall height | | 1'0" | | | | |
| Safety surfacing area | 131ft ² | | | | | |
| Total installation time | 0.5 hours | | | | | |
| Excavation volume | 0.13yd³ | | | | | |
| Concrete volume | 0.0 | 4yd³ | | | | |
| Footing depth (standard) | | 2'7" | | | | |
| Shipment weight | 3 | 88lbs | | | | |
| Anchoring options | In-ground 🗸 | | | | | |
| | Surface | ~ | | | | |
| Warranty Information | | | | | | |
| Hot dip galvanized steel | Life | etime | | | | |
| SBR rubber | 2 Y | ′ears | | | | |
| Spare Parts Availability | 10 Y | ′ears | | | | |
| | | | | | | |

| Elevated activities 0 | Accessible elevated activities | Accessible ground level activities | Accessible ground level play types |
|---------------------------------|--------------------------------------|---|---|
| Present | 0 | 1 | 1 |
| Required | 0 | 1 | 1 |







Stepping point is made of SBR rubber. It has good heat and abrasion resistance.

The steel surfaces are hot-dip galvanized inside and outside with lead-free zinc. The galvanization has excellent corrosion resistance in outside environments and requires minimal maintenance.

Sustainability Data

Cradle to Gate A1-A3

M87402-3617

M87402



Kompan A/S C.F. Tietgens Boulevard 32C DK-5220 Odense SØ Denmark



Verification of CO, calculation of: Freestanding play equipment



Data version no. 2023-10-05

The CO, calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Freestanding play equipment" represented by item no.: GXY916012-3417.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

Date: 30. October 2023 | Valid until: 30. October 2025 Verified by:

mais

Julie Marie Vejsgaard Larsen, LCA & EPD Consultant

Verification based on report: Validation of CO, calculation of 9 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Julie M. V. Larsen.

Publication date: 30. October 2023



www.bureauveritas.dk



The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))

Total CO2

emission

kg CO₂e

72.74

CO2e/kg

kg CO₂e/kg

3.91

Recycled

materials

%

22.46



M87402





12'-11" [394cm] *1' [30cm] W 6' [183cm] M87402 M87402

11" [28cm] 12'-11" [394cm] 11" [28cm] *1' / 30cm **1' / 30cm ***131.3ft² / 12.2m²



* Max fall height | ** Total height

Click to see TOP VIEW