Embankment Slide, 3.0m high, 1.5m wide

KSL30903



Item no. KSL30903-0401		
General Product Information		
Dimensions LxWxH	525x154x397 cm	
Age group	3+	
Play capacity (users)	2	
Colour options		



The extra wide Embankment Slide is extremely attractive. It makes children loop up hill and slide down again and again. The Embankment Slide will be a main attraction in a playground. Apart from the immense thrill of sliding, the Embankment Slide also supports children in developing important motor skills such as the sense of balance and space. These are important in managing the world confidently and securely. The repeated loop of sliding and running back up is great training of cardio and muscle strength. The extra width adds a highly desirable rough-and-tumble element to play, when friends go down the slide together. This is a social-emotional benefit, which is further enhanced by the cooperation skills that children use when slide together.





Embankment Slide, 3.0m high, 1.5m wide


KSL30903





Wide slide

Physical: sliding develops spatial awareness and a sense of balance. Furthermore, the core muscles are trained when sitting upright going down. Social-Emotional: invites socializing, supports parent-child and peer-to-peer play. Cognitive: young children develop their understanding of space, speed and distances when sliding down quickly.




Embankment Slide, 3.0m high, 1.5m wide






KSL30903

The stainless steel components are made of high quality stainless steel in compliance with global playground standards. The steel is glass blasted after manufacturing to ensure a smooth gliding surface.



At 35°, the slide is set to the optimum angle to ensure both gliding fun and safety.



Catering to different terrains, the embankment slides are available in 9 lengths from 1 - 3m.


Item no. KSL30903-0401		
Installation Information		
Max. fall height	100 cm	
Safety surfacing area	30.0 m²	
Total installation time	9.3	
Excavation volume	1.16 m³	
Concrete volume	0.74 m³	
Footing depth (standard)	110 cm	
Shipment weight	616 kg	
Anchoring options	In-ground 🗸	

o , , , ,	
Spare parts guaranteed	10 years
Stainless steel slide	10 years



Sustainability Data

KSL30903



Cradle to Gate A1-A3Total CO2
emissionCO2e/kgRecycled
materialskg CO2ekg CO2e/kg%KSL30903-04011,220.044.2049.98

The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))



Kompan A/S C.F. Tietgens Boulevard 32C DK-5220 Odense SØ Denmark



Verification of CO₂ calculation of: Freestanding play equipment



Data version no. 2023-10-05

The CO_2 calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Freestanding play equipment" represented by item no.: GXY916012-3417.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

Date: 30. October 2023 | Valid until: 30. October 2025 Verified by:

mais

Julie Marie Vejsgaard Larsen, LCA & EPD Consultant

Verification based on report: Validation of CO₂ calculation of 9 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Julie M. V. Larsen.

Publication date: 30. October 2023



By Bureau Veritas HSE

www.bureauveritas.dk


+45 7731 1000



KSL30903

* Max fall height | ** Total height | *** Safety surfacing area

* Max fall height | ** Total height



Click to see TOP VIEW

Click to see SIDE VIEW

5 / 06/24/2024

