

Moments Sign L, TexMade™

PCM206



With the KOMPAN signage concept, customizable signs for all kinds of outdoor activity areas are possible. Signs are essential to making relevant and prescribed information available for users in private or public places, e.g., general or practical information or instructions about the use of a playground, opening hours, ideal user/age groups,

sponsors, contact information, etc.

KOMPAN's customizable signage concept is flexible in using text, signs, and symbols to communicate a message. Selected products with low carbon emissions are available in GreenLine versions and are made mainly from post-consumer ocean waste.

Item no. PCM206-0650	
General Product Information	
Dimensions LxWxH	2'4"x0'4"x4'11"
Age group	
Play capacity (users)	
Color options	



Moments Sign L, TexMade™

PCM206



Main posts with hot-dip galvanized steel footing are available in different materials: Pressure impregnated pinewood posts. Pre-galvanized inside and outside with powder-coated top finish steel posts. Lead-free aluminum with color anodized top finish. Greenline TexMade posts of 100% post-consumer recycled PE and textile waste.



High-quality polycarbonate with a thickness of 8mm. The graphic prints are added by a unique multi-layer print process where the inner layer is the image and outer transparent layer functions as protection. Both PC panel and the water-based lacquer are UV stabilized to prevent fading.

Item no. PCM206-0650	
Installation Information	
Total installation time	1.4
Excavation volume	0.05yd³
Concrete volume	0yd³
Footing depth (standard)	2'0"
Shipment weight	174lbs
Anchoring options	In-ground ✓
Warranty Information	
Polycarbonate PC panels	10 Years
Post	10 Years
Spare Parts Availability	10 Years

Sustainability Data

PCM206



Cradle to Gate A1-A3	Total CO ₂ emission	CO ₂ e/kg	Recycled materials
	kg CO ₂ e	kg CO ₂ e/kg	%
PCM206-0650	161.76	2.69	55.70

The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))

Kompan A/S
C.F. Tietgens Boulevard 32C
DK-5220 Odense SØ
Denmark



Verification of CO₂ calculation of:
Park



Data version no. 2023-10-05

The CO₂ calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Park" represented by item no.: PAR4070-0001.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

Date: 30. October 2023 | Valid until: 30. October 2025
Verified by:

Julie Marie Vejsgaard Larsen, LCA & EPD Consultant

Verification based on report: Validation of CO₂ calculation of 9 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Julie M. V. Larsen.

Publication date: 30. October 2023

By Bureau Veritas HSE
www.bureauveritas.dk
+45 7731 1000

