# Step, 40cm

FPW302



Item no. FPW3	0200-0900	
General Product Information		
Dimensions LxWxH	58x39x39 cm	
Age group	8+	
Play capacity (users)	1	
Color options		






The step is one of the most simple yet highly versatile training tools, so many exercises can be done with it, from simple step ups to plyometric jumps. Regular sessions will provide both cardiovascular and muscular endurance. Incorporating upper and lower body movements will improve balance and agility, and the constant push up onto the step will increase leg strength

# Step, 40cm








A 5 mm hot-dip galvanised carbon steel plate must is moulded inside the SBR to offer optimal stability and optimize the mounting of the step to the frame.

The support frame is ø48.3 x 4mm, carbon steel, with a hot-dip galvanised surface according to ISO1461, and a powder coating corrosion class C3 according to ISO12944-2. Lead content for surfaces are below 90ppm.



The surface is produced of recycled SBR (Styrene Butadiene Monomer, Synthetic Rubber) for optimal grip during jumping and step on step off exercises under all weather circumstances.

Item no. FPW30200-0900			
Installation Information			
Max. fall height	3	9 cm	
Safety surfacing area	10.4 m²		
Total installation time	1.3		
Excavation volume	0.13 m³		
Concrete volume	0.07 m³		
Footing depth (standard)	90 cm		
Shipment weight	(	61 kg	
Anchoring options	In-ground	~	
	Surface	~	



## **Sustainability Data**

Cradle to Gate A1-A3


FPW30200-0900

FPW302



Kompan A/S C.F. Tietgens Boulevard 32C DK-5220 Odense SØ Denmark







#### Data version no. 2023-10-05

The  $CO_2$  calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Fitness" represented by item no.: FAZ10100-0900.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

Date: 30. October 2023 | Valid until: 30. October 2025 Verified by:

### mais

Julie Marie Vejsgaard Larsen, LCA & EPD Consultant

Verification based on report: Validation of CO<sub>2</sub> calculation of 9 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Julie M. V. Larsen.

Publication date: 30. October 2023

By Bureau Veritas HSE www.bureauveritas.dk +45 7731 1000



The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))

**Total CO2** 

emission

kg CO<sub>2</sub>e

75.14

CO2e/kg

kg CO<sub>2</sub>e/kg

1.80

Recycled


materials

%


65.89




FPW302



KOMPAN Let's play





\* Max fall height | \*\* Total height

Click to see TOP VIEW

4 / 08/02/2024