
Baby Seat, H:2.0m

SW990022



Item no. SW990022-00		
General Product Information		
Dimensions LxWxH	63x37x140 cm	
Age group	1+	
Play capacity (users)	1	
Color options	•	





seat is placed in a good height for the infant to be in eye level with children. The swinging motion trains the child's motor skills, specifically the sense of balance and space. Seated while swinging also trains the core muscles. All of these physical skills are fundamental to the infants ability to walk and navigate the surroundings securely. The action also stimulates the understanding of cause and effect and thinking skills. Socially, swinging and getting pushed in the swing seat by parents, care givers or siblings is great fun.



SW990022





Toddler swing seat Physical: balance, coordination and spatial awareness are developed when swinging. These are necessary skills for judging distances and navigating. Social-Emotional: feeling of security from support. Cognitive: understanding of cause and effect.



Baby Seat, H:2.0m

SW990022



The baby seat is a two component seat with a PP inner core and outside rubber, produced in one operation. The seat is available with swing chains of either hot dip galvanised steel or stainless steel.



Item no. SW990022-00		
Installation Information		
Max. fall height	0 cm	
Safety surfacing area	12.3 m²	
Total installation time	0.1	
Excavation volume	0.00 m³	
Concrete volume	0.00 m³	
Footing depth (standard)	0 cm	
Shipment weight	6 kg	
Anchoring options		



Sustainability Data

Cradle to Gate A1-A3

SW990022-00

SW990022



Kompan A/S C.F. Tietgens Boulevard 32C DK-5220 Odense SØ Denmark



Verification of CO, calculation of: Freestanding play equipment



Data version no. 2023-10-05

The CO₂ calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Freestanding play equipment" represented by item no.: KSW92011-0910.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

Date: 30. October 2023 | Valid until: 30. October 2025 Verified by:

mais

Julie Marie Vejsgaard Larsen, LCA & EPD Consultant

Verification based on report: Validation of CO, calculation of 9 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Julie M. V. Larsen.

Publication date: 30. October 2023



www.bureauveritas.dk



The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))

Total CO2

emission

kg CO₂e

19.30

CO2e/kg

kg CO₂e/kg

4.31

Recycled

materials

%

17.94




SW990022

* Max fall height | ** Total height | *** Safety surfacing area




* Max fall height | ** Total height



SW990022

***12.3m²



SW990022 1:100

Click to see SIDE VIEW