Stinger ELE400020



Item no. ELE400020-01E		
General Product Information		
Dimensions LxWxH	78x37x70 cm	
Age group	2+	
Play capacity (users)	1	
Color options		



The Stinger with it's whimsical, rodeo look attracts toddlers for a shorter or longer ride, again and again. Apart from its appealing shapes, the Stinger offers tactile variation with its rubber hand holds and smooth body. Tactile richness is the main motivator, especially in younger children. It supports their understanding of material characteristics such as weight, smoothness, temperature and flexibility. The slightly sloped seat provides a seating destination which ensures hours, years and decades of fun. The soothing, rocking movement of the Stinger trains the sense of balance and the spatial awareness. These are both crucial for body confidence, e.g. fall prevention. A well-developed sense of balance is fundamental for the ability to sit still and concentrate. The Stinger offers children more than a mere fun ride.





Stinger

ELE400020





The seat is made with recycable PE from 33% post consumer materials and moulded in one piece with a minimum 5mm wall thickness. PE has high impact resistance across a wide temperature span which ensures vandal resistance in all locations.



KOMPAN Springs are made of high quality

are cleaned by phosphating before they are

painted with an epoxy primer and a polyester

powder coating as top finish. The springs are

fixed by unique anti pinch fittings for maximum

spring steel according to EN10270. The springs



The springs are fixed by unique anti pinch fittings for maximum safety and long lifetime.

Item no. ELE400020-01E			
Installation Information			
Max. fall height		60 cm	
Safety surfacing area		5.8 m²	
Total installation time		1.9	
Excavation volume	0	.19 m³	
Concrete volume	0	.00 m³	
Footing depth (standard)		45 cm	
Shipment weight		35 kg	
Anchoring options	In-ground	~	
	Surface	~	



Handles are made with a moulded PP insert and an outer layer of soft TPV rubber. The handles are attached to the pipe with a galvanised steel inlay to ensure strength and durability.



safety and long lifetime.

The steel surfaces are hot dip galvanised inside and outside with lead free zinc. The galvanisation has excellent corrosion resistance in outside environments and requires low maintenance.



KOMPAN GreenLine versions are designed with ultimate environmentally friendly materials with lowest possible CO2e emission factor such as EcoCoreTM panels of +95% post consumer recycled ocean waste.



Sustainability Data

Cradle to Gate A1-A3

ELE400020-01E

ELE400020



Kompan A/S C.F. Tietgens Boulevard 32C DK-5220 Odense SØ Denmark



Verification of CO₂ calculation of: Freestanding play equipment



Data version no. 2023-10-05

The CO_2 calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Freestanding play equipment" represented by item no.: GXY916012-3417.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

Date: 30. October 2023 | Valid until: 30. October 2025 Verified by:

mais

Julie Marie Vejsgaard Larsen, LCA & EPD Consultant

Verification based on report: Validation of CO₂ calculation of 9 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Julie M. V. Larsen.

Publication date: 30. October 2023



The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))

Total CO2

emission

kg CO₂e

76.40

CO2e/kg

kg CO₂e/kg

2.54

Recycled

materials

%

42.10




ELE400020


* Max fall height | ** Total height | *** Safety surfacing area



* Max fall height | ** Total height



ELE400020 *60cm **70cm ***5.8m²



ELE400020

Click to see TOP VIEW

Click to see SIDE VIEW

4 / 04/22/2024