



# Cave Trail

CRP252201

Item no. CRP252201-0902	
General Product Information	
Dimensions LxWxH	63'3"x53'11"x15'2"
Age group	5 - 12
Play capacity (users)	100
Color options	



The Cave Trail provides highly attractive challenges for children, which make them want to come back again and again. The rich variety of balancing, swaying, spinning and climb-and-crawl activities are great to help develop children's sense of balance, coordination and proprioception, which is fundamental for managing a range of life skills in the future.

When playing "the ground is made of lava" on the exciting loops, children develop motor skills and muscles. But they also use and build important social-emotional skills such as turn-taking, empathy, teamworking and communication. Outside the loops, the Musca Spinner trains upper body muscles and is great for the understanding of rotation principles,

whereas the Sputnik invites for a break and socialising. The trail offers graded play challenges, and the slide invites a fun egress back to ground level. This is the favourite way of older children to connect, communicate and cooperate, and make friendships for life.

# Cave Trail

CRP252201



## Satellite spinner

**Physical:** balance when standing, sitting and rotating, muscles develop when holding tight.  
**Social-Emotional:** turn-taking, socializing.  
**Cognitive:** logical thinking, figuring out how to make the spinner work with gravity, not against it.




## Trapezoid climber

**Physical:** the bouncy membrane trains the sense of balance, which is fundamental for movement control. The inclined membranes motivate climbing, which trains cross-body coordination. Arm, leg and core muscles are strengthened, too. **Social-Emotional:** cooperation, sharing and empathy are developed when children play together on the bouncy membranes.



## Hurdles

**Physical:** arm, leg and core muscles are developed when climbing up or through. Balance and spatial awareness, motor skills that help in judging the body in space. **Social-Emotional:** cooperation and turn-taking when passing one another.



## Shaky pods rope

**Physical:** sense of balance and space, and training of posture. Important for being able to sit still. **Social-Emotional:** cooperation, turn-taking and friendly competition on the plates.




## Zig-zag slider

**Physical:** muscle strength, balance and coordination when climbing up and down, holding tight.



## Curved slide

**Physical:** sliding develops spatial awareness and a sense of balance. Furthermore, the core muscles are trained when sitting upright going down. **Social-Emotional:** empathy stimulated by turn-taking.



## Cube net

**Physical:** agility, balance and coordination as well as spatial awareness are supported when bouncing, climbing and sitting in the net. Children train their arm, leg and core muscle strength. **Social-Emotional:** great meeting point that invites socializing and sharing.

# Cave Trail

CRP252201



Ropes are made of UV-stabilized PES rope strands with inner steel cable reinforcement. The polyester wrapping is inductively melted onto each strand to ensure excellent wear and tear resistance.



Corocord 'S' clamps are used as universal connections in Corocord products. 8mm stainless steel rods with rounded edges are pressed around the ropes with a special hydraulic press, making them the ideal connector: safe, durable and vandalism-proof, all while allowing the typical movement of rope play structures.



Panels of 19mm EcoCore™. EcoCore™ is a highly durable, eco friendly material, which is not only recyclable after use, but also consists of a core produced from 100% recycled material.

Item no. CRP252201-0902	
Installation Information	
Max. fall height	9'6"
Safety surfacing area	3312ft <sup>2</sup>
Total installation time	90.9
Excavation volume	60.78yd <sup>3</sup>
Concrete volume	35.12yd <sup>3</sup>
Footing depth (standard)	2'11"
Shipment weight	7103lbs
Anchoring options	Surface ✓ In-ground ✓
Warranty Information	
Aluminum clamps	10 Years
Hot dip galvanized steel	Lifetime
Painted toplayer	10 Years
Ropes & nets	10 Years
Spare Parts Availability	10 Years



Colored steel components have a base of hot dip galvanization and a powder coated top finish. This provides an ultimate corrosion resistance in all climates around the world. Other steel surfaces are hot dip galvanized inside and outside with lead free zinc.



The Corocord Smart Clamps are carefully designed to ensure superior flexibility in high-quality aluminum material. The smart clamps are attached around the post with four steel bolts. Unused attachment points are closed with PA caps.



Slide is made of molded PE. PE has excellent impact strength and it is usable within a large temperature span.

Elevated activities 2	Accessible elevated activities	Accessible ground level activities	Accessible ground level play types
Present	2	2	2
Required	1	1	1

**ASTM  
F1487**  
compliant



# Sustainability Data

CRP252201



Cradle to Gate A1-A3	Total CO <sub>2</sub> emission	CO <sub>2</sub> e/kg	Recycled materials
	kg CO <sub>2</sub> e	kg CO <sub>2</sub> e/kg	%
<b>CRP252201-0902</b>	9,540.30	3.36	45.00

The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))

**Kompan A/S**  
 C.F. Tietgens Boulevard 32C  
 DK-5220 Odense SØ  
 Denmark



## Verification of CO<sub>2</sub> calculation of: Corocord



Data version no. 2023-10-05

The CO<sub>2</sub> calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Corocord" represented by item no.: COR314011-1101.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

**Date: 30. October 2023 | Valid until: 30. October 2025**

Verified by:

Julie Marie Vejsgaard Larsen, LCA & EPD Consultant

Verification based on report: Validation of CO<sub>2</sub> calculation of 9 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Julie M. V. Larsen.

**Publication date: 30. October 2023**

By Bureau Veritas HSE  
 www.bureauveritas.dk  
 +45 7731 1000




# Cave Trail


CRP252201

\* Max fall height | \*\* Total height | \*\*\* Safety surfacing area

\* Max fall height | \*\* Total height



CRP252201  
\* 9'-6" / 290cm  
\*\* 15'-2" / 463cm  
\*\*\* 3312.1ft<sup>2</sup> / 307.7m<sup>2</sup>



[Click to see TOP VIEW](#)

[Click to see SIDE VIEW](#)