

COR10481





The Circite With House Membrane is a threedimensional rope environment in which the child can move freely in all directions ensuring hours of play. Inside the construction, children can prove their climbing skills on the rope, while the frame and long ropes at the sides are perfectly suited for hanging. Muscle strength, cross-body coordination and spatial awareness are trained. These skills are fundamental e.g. when judging distances and managing traffic securely. Apart from physical stimulation, membranes allow children to sit and talk, socializing.








COR10481







Height Social-Emotional: children develop courage and self-regulation when being up high. This positively affects self-confidence.









Membrane path

Physical: a faster way up, due to the extra support of the membrane. **Social-Emotional:** a meeting path with points for retreat from the rope landscape.







Connected nets

Physical: the connected nets make the climbers feel the movements of the others, adding a dimension of fun and demanding concentration when holding tight to the rope. Cross-coordination and all muscle groups are trained. Social-Emotional: the climbers' movements affect the other climbers, so consideration and turn-taking is supported.





Transparency

Social-Emotional: the transparency makes possible cooperation and communication throughout, all important life-skills for children to learn.







Big meshes

Physical: the big meshes allow for climbing and crawling, supporting proprioception, cross coordination and spatial awareness. Climbing here takes muscle strength, pushing and pulling arms to get upwards. Social-Emotional: allow more children being seated together, sharing.

COR10481



In-ground



Corocord 'S' clamps are used as universal connections in Corocord products. 8mm stainless steel rods with rounded edges are pressed around the ropes with a special hydraulic press, making them the ideal connector: safe, durable and vandalism-proof, all while allowing the typical movement of rope play structures.



The aluminium swages of the net are double conical with rounded ends and are as small as safety allows. The overall net design aims at keeping metal parts within the net to an absolute minimum, both in size and number, in order to provide the best possible rope climbing experience.



Corocord membranes consist of friction-proof rubberized material of conveyor belt quality with excellent UV resistance. Tested and compliant with REACH requirements for PAH. Embedded is a four-layered armouring made of woven polyester. The armouring and the two surface layers result in a total thickness of 7.5 mm.



Item no. COR104811-0405

Installation Information			
Max. fall height	300 cm		
Safety surfacing area	42.4 m ²		
Total installation time	21.3		
Excavation volume	1.76 m ³		
Concrete volume	0.98 m ³		
Footing depth (standard)	90 cm		
Shipment weight	776 kg		

Warranty Information			
Corocord rope	10 years		
EcoCore HDPE	Lifetime		
Hot dip galvanised steel	Lifetime		
Membrane	2 years		
Spare parts guaranteed	10 years		



The metal parts are made of high quality steel, hot dip galvanised inside and outside with leadfree zinc. On the outside, there is an additional layer of powder coating. This ensures both excellent corrosion resistance and colourful design expression.



VENUS

MARS









TERRA NEPTUNE

The COROCORD Frame Nets are available in 6 galactic colour themes. The themes draw on bright colours that appeal to children of all ages. Can be changed in the configurator.

Elevated activities 0	Accessible elevated activities	Accessible ground level activities	Accessible ground level play types
Present	0	1	1
Required	0	1	1




Anchoring options

3 / 05/23/2024 Data is subject to change without prior notice.

Sustainability Data

COR10481





Cradle to Gate A1-A3	Total CO₂ emission CO₂e/kg		Recycled materials
	kg CO₂e	kg CO₂e/kg	%
COR104811-0405	1,986.85	4.00	37.30

The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))

Kompan A/S

C.F. Tietgens Boulevard 32C DK-5220 Odense SØ Denmark



Verification of CO₂ calculation of: Corocord



Data version no. 2023-10-05

The CO_2 calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Corocord" represented by item no.: $\mathrm{COR314011}$ -1101.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

Date: 30. October 2023 | Valid until: 30. October 2025 Verified by:

Julie Marie Vejsgaard Larsen, LCA & EPD Consultant

Verification based on report: Validation of CO_2 calculation of 9 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Julie M. V. Larsen.

Publication date: 30. October 2023


By Bureau Veritas HSE www.bureauveritas.dk +45 7731 1000


COR10481



* Max fall height | ** Total height | *** Safety surfacing area

* Max fall height | ** Total height





Click to see SIDE VIEW