COR88100





General Product Information

Dimensions LxWxH 400x400x330 cm
Age group 5+
Play capacity (users) 32
Colour options



The eight-legged, spider-like Miracle Sphere is a popular playscape keeping children occupied for hours with its webs of diverse climbing opportunities. The swaying ropes, nets and rubber ladders offer fun climbing challenges to the vertical top net. With its spread out access points to the top net, the Miracle Sphere caters for a lot of children in fun play at the same time.

Apart from being great fun, the Miracle Sphere offers ample training of all major muscles and fundamental motor skills. All muscles are in use when clinging on to the ropes or climbing up high. Important motor skills such as cross-body coordination and spatial awareness are used. These skills are fundamental e.g. when judging distances and managing traffic securely. The

horizontal top net is a great venue for meeting friends, socialising and helping one another up find a way up to chill and enjoy the view.



COR88100









Horizontal net

Physical: cross coordination is developed when climbing over and sense of space when looking down. Social-Emotional: space for socialising and bouncy breaks.









Big meshes


Physical: the big meshes allow for climbing and crawling, supporting proprioception, cross coordination and spatial awareness. Social-Emotional: allow more children being seated together, sharing.



Connected nets









pass each other.



coordination and muscle strength when using

Social-Emotional: turn-taking when children

the rope to climb the steps. Their sense of

Vertical side ropes with steps

Physical: children develop cross-body

balance is trained when swaying gently.





Membrane loops

Physical: develops leg, arm and core muscles as well as motor skills such as cross coordination and proprioception. Social-**Emotional:** showing consideration of others and helping others when passing one another going up or down.



Transparency Social-Emotional: the transparency makes

cooperation and communication possible, which are essential life skills for children to learn.









Physical: children develop cross-body coordination and muscle strength when climbing the rope. Their sense of balance is trained when swaying gently. Social-Emotional: socialising and turn-taking when

deciding who should sit here.

COR88100






Corocord membranes consist of friction-proof rubberised material of conveyor belt quality with excellent UV resistance. Tested and compliant with REACH requirements for PAH. Embedded is a four-layered armouring made of woven polyester. The armouring and the two surface layers result in a total thickness of 7.5 mm.



Corocord aluminium clamps are used as connectors between steel posts and rope. The aluminium casting is screwed into the steel post and connects safely to the rope.



Fully coloured EPDM rubber discs with smooth surface. The moulded EPDM surrounds a hotdip galvanised steel core that ensures both the stability of the discs and durable fixtures to the rope.



Item no. COR881001-0402

| Installation Information | | | | |
|--------------------------|-----------|------|--|--|
| Max. fall height | 240 | cm | | |
| Safety surfacing area | 48.5 | 5 m² | | |
| Total installation time | 2 | 27.1 | | |
| Excavation volume | 6.32 | 2 m³ | | |
| Concrete volume | 2.43 | 3 m³ | | |
| Footing depth (standard) | 65 | cm | | |
| Shipment weight | 1,076 | ∂ kg | | |
| Anchoring options | In-ground | • | | |

| Warranty Information | | | |
|-----------------------------|----------|--|--|
| Aluminium Clamps | 10 years | | |
| Corocord (Hercules) Rope | 10 years | | |
| Membrane | 2 years | | |
| S-Clamps | 10 years | | |
| Spare Parts Guarantee | 10 years | | |



Corocord ropes with 19mm+ diameter are known as a 'Hercules' rope type which is formed from galvanised six-stranded steel wires. Each strand is tightly wrapped with PES yarn, which is melted onto each individual strand. Ropes are highly wear-and vandalism-resistant and can be easily replaced on-site if needed.



Designed to allow the typical function of rope play structures to move Corocord 'S' clamps are used as universal connections in Corocord products. 8mm stainless steel rods with rounded edges are pressed around the ropes with a special hydraulic press, making them the ideal connector. Our clamps are safe, durable and vandalism-proof.




3 / 11/14/2024 Data is subject to change without prior notice.

Sustainability Data

COR88100





| Cradle to Gate A1-A3 | Total CO₂ emission | CO₂e/kg | Recycled materials |
|----------------------|-----------------------|------------|--------------------|
| | kg CO₂e | kg CO₂e/kg | % |
| COR881001-0402 | 2,889.58 | 3.16 | 47.05 |

The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))

Kompan A/S

C.F. Tietgens Boulevard 32C DK-5220 Odense SØ Denmark



Verification of CO₂ calculation of: Corocord



Data version no. 2023-10-05

The CO_2 calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Corocord" represented by item no.: $\mathrm{COR314011}$ -1101.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

Date: 30. October 2023 | Valid until: 30. October 2025 Verified by:

mode

Julie Marie Vejsgaard Larsen, LCA & EPD Consultant

Verification based on report: Validation of CO_2 calculation of 9 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Julie M. V. Larsen.

Publication date: 30. October 2023

By Bureau Veritas HSE www.bureauveritas.dk +45 7731 1000





COR88100

KOMPAN Let's play

* Max fall height | ** Total height | *** Safety surfacing area

* Max fall height | ** Total height





Click to see TOP VIEW

Click to see SIDE VIEW