
## **Mini Dome with Slide**

CRP810201



Item no. CRP810201-0903			
General Product Information			
Dimensions LxWxH	750x740x255 cm		
Age group	2 - 5		
Play capacity (users)	42		
Colour options			



Marvelous Mini Dome amazes children with its richness in play variation and detail, again and again. The Dome can be entered from all over: bouncy membranes, nets, climbing ropes, and stairs take the toddlers to the top membrane circle. This bouncing viewpoint invites friends to meet. Under it, a cozy den is created with varied climb or peep-through membranes that

invite play classics such as peek-a-boo. The panels and hammock around the central nets allow for dramatic play and exploration with sensory details. The slide is a play magnet and completes the play offerings that train motor skills such as balance, coordination and proprioception. These are fundamental in moving the body confidently and securely. The varied movements additionally instill an understanding of space, shapes, and measures which is fundamental for understanding mathematics. The Mini Dome offers great play capacity, so children learn turn-taking skills through play and make friends that way.

# **Mini Dome with Slide**

CRP810201





Inclined net with membrane Physical: the inclined net supports the upward climbing movement of the body, which stimulates cross-body coordination and muscle strength. The bouncy membrane develops the sense of balance when children jump, stand or sit here. Social-Emotional: the big net allows for more children to be active together, seated or lying.





#### Double slide

Physical: sliding develops spatial awareness and a sense of balance. Furthermore, the core muscles are trained when sitting upright going down. Social-Emotional: invites socializing, supports parent-child and peer-to-peer play. Cognitive: young children train their understanding of space, speed and distances when sliding down quickly.



#### Mirror

**Cognitive:** understanding of individuality and self expression. Stimulates dramatic play and thus language and communication development.



#### Window with curtains

Physical: tactile stimulation supports sensory skills, when children explore characteristics of the materials. Social-Emotional: social interaction between inside and outside, supporting turn-taking and cooperation. Cognitive: understanding object permanence when playing, e.g. peek-a-boo. Dramatic play support, encouraging language skills. Creative: leaving a mark, deciding how to place curtains.



Abacus Cognitive: supports understanding of measures.



### Top circular membrane

Physical: the sense of balance and space is supported when entering the slightly bouncing membrame. This trains the understanding of time, space and measures important in moving the body in securely. Social-Emotional: children develop courage when climbing and being up high. This positively affects self-confidence. The top membrane provides a great place to be together with friends.



#### Crawl-through hole

Physical: the hole allows for climbing and crawling through, developing cross coordination, proprioception and spatial awareness. Social-Emotional: cooperation and turn-taking when passing one another. Cognitive: understanding space, shape and measures when seeing if the body can fit through the hole.

### **Mini Dome with Slide**



CRP810201



Panels of 19mm EcoCore<sup>™</sup>. EcoCore<sup>™</sup> is a highly durable, eco friendly material, which is not only recyclable after use, but also consists of material produced from +95% recycled post consumer material from food packing waste.



The steel arches are hot dip galvanised inside and outside with lead free zinc. The galvanisation has excellent corrosion resistance in outside environments and requires low maintenance.



The slides can be chosen in six different colors and two materials: Molded PE slides made with 33% post consumer materials or full stainless steel in one-piece design for more vandalism proof solutions.

Item no. CRP810201-0903				
Installation Information				
Max. fall height	16	63 cm		
Safety surfacing area	85	5.6 m²		
Total installation time		36.6		
Excavation volume	9.	08 m³		
Concrete volume	4.8	83 m³		
Footing depth (standard)	ę	90 cm		
Shipment weight	1,0	10 kg		
Anchoring options	In-ground	~		
	Surface	~		
Warranty Information				
Corocord rope	10	years		
EasCara HDDE	l if	otimo		

Corocord rope	10 years
EcoCore HDPE	Lifetime
Hollow PE parts	10 years
Hot dip galvanised steel	Lifetime
Spare parts guaranteed	10 years



Ropes of UV-stabilized PES rope strands with inner steel cable reinforcement. The polyester yarn is made of +95% Post-consumer materials and is inductively melted onto each strand to obtain excellent wear and tear resistance.



Corocord 'S' clamps are used as universal connections in Corocord products. 8mm stainless steel rods with rounded edges are pressed around the ropes with a special hydraulic press, making them the ideal connector: safe, durable and vandalism-proof, all while allowing the typical movement of rope play structures.



Corocord smart clamps are carefully designed in every detail to ensure superior flexibility in high quality aluminum material. The smart clamps are attached around the posts with four steel bolts. Not used attachment points are closed with PA caps.

	Elevated activities <b>2</b>	Accessible elevated activities	Accessible ground level activities	Accessible ground level play types
	Present	2	5	3
	Required	1	1	1

CSA Z614 compliant

## **Sustainability Data**

CRP810201



Cradle to Gate A1-A3	Total CO₂ CO₂e/kg emission		Recycled materials
	kg CO₂e	kg CO₂e/kg	%
CRP810201-0903	2,140.96	2.88	50.81

The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))



Kompan A/S C.F. Tietgens Boulevard 32C DK-5220 Odense SØ Denmark



Verification of CO<sub>2</sub> calculation of: Corocord



Data version no. 2023-10-05

The  $CO_2$  calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Corocord" represented by item no.: COR314011-1101.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

Date: 30. October 2023 | Valid until: 30. October 2025 Verified by:

maiz

Julie Marie Vejsgaard Larsen, LCA & EPD Consultant

Verification based on report: Validation of CO<sub>2</sub> calculation of 9 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Julie M. V. Larsen.

Publication date: 30. October 2023



Data is subject to change without prior notice.

+45 7731 1000

**By Bureau Veritas HSE** 

www.bureauveritas.dk





CRP810201

\* Max fall height | \*\* Total height | \*\*\* Safety surfacing area



\* Max fall height | \*\* Total height





Click to see TOP VIEW

Click to see SIDE VIEW

5 / 01/23/2025