

# Moments Sign XL, TexMade™

PCM207



With the KOMPAN signage concept it's possible to create customisable signs for all kinds of outdoor activity areas. Signs are an important way to make relevant and prescribed information available for the users of private or public areas. E.g. general or practical information or instructions about the use of a playground, opening hours, ideal user/age

groups, sponsors, contact information etc. KOMPAN's customisable signage concept is flexible in the use of text, signs and symbols to communicate a message. Selected products are available in GreenLine versions, with low carbon emission, made mainly from post-consumer ocean waste.

|                  |               |
|------------------|---------------|
| 产品编号 PCM207-0950 |               |
| 产品信息概览           |               |
| 长宽高尺寸            | 106x11x215 cm |
| 适用年龄段            |               |
| 容纳人数             |               |
| 颜色选择             |               |



# Moments Sign XL, TexMade™

PCM207



具有热镀锌钢脚的主立柱有不同的材料可供选择：压力浸渍松木立柱；在内外部进行了预镀锌处理，顶部涂有粉末涂层的钢柱；无铅铝，表面彩色阳极氧化处理；环保产品 TexMade 立柱，100% 消费后再生的 PE 和纺织废料制成。

厚度为 8mm 的优质聚碳酸酯。图形文字通过独特的多层打印工艺添加，内层为图像，外部透明层起保护作用。PC 面板和水性漆均经过紫外线稳定处理，可防止褪色。

| 产品编号 PCM207-0950 |    |         |
|------------------|----|---------|
| 安装信息             |    |         |
| 安装总时长            |    | 2.2     |
| 开挖量              |    | 0.06 m³ |
| 混凝土使用量           |    | 0.00 m³ |
| 标准入地深度           |    | 85 cm   |
| 运输重量             |    | 161 kg  |
| 固定选项             | 入地 | ✓       |
| 质保信息             |    |         |
| 聚碳酸酯 PC 面板       |    | 10 年    |
| 立柱               |    | 10 年    |
| 承保零部件            |    | 10 年    |

# Sustainability Data

PCM207



| 从原材料到成品     | CO <sub>2</sub> 排放总量 | CO <sub>2</sub> 排放量 / 千克 | 回收的原料 |
|-------------|----------------------|--------------------------|-------|
|             | kg CO <sub>2</sub> e | kg CO <sub>2</sub> e/kg  | %     |
| PCM207-0950 | 463.81               | 3.73                     | 38.58 |

这些因素采用的总体框架为环保产品声明 (EPD)，该声明可量化“产品生命周期的环保信息，并对相同功能的产品进行对比” (ISO, 2006)。在遵循该框架的同时，对从原材料到制造的整个产品阶段 (A1-A3) 应用生命周期评估法。

## Kompan A/S

C.F. Tietgens Boulevard 32C  
DK-5220 Odense SØ  
Denmark



## Verification of CO<sub>2</sub> calculation of: Park



Data version no. 2023-10-05

The CO<sub>2</sub> calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Park" represented by item no.: PAR4070-0001.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

**Date: 30. October 2023 | Valid until: 30. October 2025**

**Verified by:**

Julie Marie Vejsgaard Larsen, LCA & EPD Consultant

Verification based on report: Validation of CO<sub>2</sub> calculation of 9 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Julie M. V. Larsen.

**Publication date: 30. October 2023**

By Bureau Veritas HSE  
www.bureauveritas.dk  
+45 7731 1000

