

Combi 3

FSW103



This overhead ladder is wide and high to ensure anyone can hang and move freely. To make sure that everyone can reach the overhead ladder we added 4 stepping pods at different heights. The complete street workout experience, features all essential elements while inviting users to creatively find their way from one side to the other. As such, the Combi

3 is perfect for parkour, allowing for an infinite range of movements. The Pull Up Bar is made from solid steel and has a diameter 1 1/4", an ideal size for both men and women to have a good grip. As the Bar hangs at an height 7'8", everyone will be able to hang freely and use the bar for a variety of Pull Ups.

Item no. FSW10301-0901

General Product Information

Dimensions LxWxH 23'10"x14'3"x7'10"

Age group 13+

Play capacity (users) 8

Color options 



See KOMPAN Fit App for More Information



Combi 3


FSW103



Post are made of 101.6 x 2mm, pre-galvanized carbon steel and powder coated, a great protection to all conditions.



The connectors are made of die-cast aluminium, specially alloyed for the outdoor environments and heavy usage. The screws attaching the connectors are stainless steel and protected by zinc washers.



All bars intended for pull ups are made of solid, ø32mm x 138 m, hot dip galvanized, S235JR steel bars. This diameter gives the right grip for everyone.



The handles offer 4 different heights to place the hands or feet; 48cm, 76cm, 104cm and 132cm, creating the opportunity to scale the difficulty of the exercise.



The information sign is made of a PA6 (Polyamide) and shows the most relevant exercise and a QR code. When scanned the QR code will link to an animated illustration of the exercise and offers the possibility of downloading the KOMPAN sport & fitness App, which will provide a large amount of exercises and workouts.



The ropes are made of UV-stabilised PES with inner steel cable reinforcement. The rope is induction treated in order to create a strong connection between steel and rope which leads to good wear resistance.

Item no. FSW10301-0901

Installation Information

Max. fall height	7'8"
Safety surfacing area	443ft ²
Total installation time	8.6
Excavation volume	0.99yd ³
Concrete volume	0.56yd ³
Footing depth (standard)	2'11"
Shipment weight	660lbs
Anchoring options	In-ground ✓ Surface ✓


Warranty Information

Connectors	10 Years
Hot dip galvanized steel	Lifetime
Post	10 Years
Ropes & nets	10 Years
Spare Parts Availability	10 Years

**ASTM
F3101**
compliant

Sustainability Data

FSW103



Cradle to Gate A1-A3	Total CO ₂ emission	CO ₂ e/kg	Recycled materials
	kg CO ₂ e	kg CO ₂ e/kg	%
FSW10301-0901	849.71	3.52	48.01

The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))

Kompan A/S
 C.F. Tietgens Boulevard 32C
 DK-5220 Odense SØ
 Denmark



Verification of CO₂ calculation of: Fitness



Data version no. 2023-10-05

The CO₂ calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Fitness" represented by item no.: FAZ10100-0900.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

Date: 30. October 2023 | Valid until: 30. October 2025

Verified by:

Julie Marie Vejsgaard Larsen, LCA & EPD Consultant

Verification based on report: Validation of CO₂ calculation of 9 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Julie M. V. Larsen.

Publication date: 30. October 2023

By Bureau Veritas HSE
 www.bureauveritas.dk
 +45 7731 1000





Combi 3

FSW103

* Max fall height | ** Total height | *** Safety surfacing area

* Max fall height | ** Total height



[Click to see TOP VIEW](#)

[Click to see SIDE VIEW](#)