Over Under


FSW214





Trained athletes will go over the high bar and underneath the low bar, while the beginners will do it the other way around. A great way to train, strength, agility, coordination and flexibility. The Over Under obstacle is a great example that everyone can be challenged at their own level. The bars are positioned closely to another therefore a combination of lower body and

upper body strength is required to overcome this obstacle. Rounded corners make it safe and simple for anyone to try exercises in which they swing over their legs over the bar.





See KOMPAN Fit app for more



Over Under

FSW214



10 years



Post are made of Ø101.6 x 2mm, pregalvanized carbon steel and powder coated, a great protection to all conditions.




The connectors are made of die-cast aluminium, specially alloyed for the outdoor environments and heavy usage. The screws attaching the connectors are stainless steel and protected by zinc washers.



Bars intended as grips during exercises are made of hot-dip galvanised steel ø38mm. A great diameter to support the wrist when doing dips or handstands.

Item no. FSW21400-0900			
Installation Information			
Max. fall height	118	3 cm	
Safety surfacing area	28.	1 m²	
Total installation time		3.7	
Excavation volume	0.2	3 m³	
Concrete volume	0.1	2 m³	
Footing depth (standard)	90 cm		
Shipment weight	16	3 kg	
Anchoring options	In-ground	•	
	Surface	>	
Warranty Information			
Hot dip galvanised steel	Lifetime		
Post	10 years		



All KOMPAN fitness products are compliant with the ASTM F3101 & EN16630 Outdoor Fitness Standards. Load tests are performed as a static test by adding dynamic factors as well as safety factors to the specified load of 78kg per user. A product intended for 1 user is loaded with 420kg.



The information sign is made of a PA6 (Polyamide) and shows the most relevant exercise and a QR code. When scanned the QR code will link to an animated illustration of the exercise and offers the possibility of downloading the KOMPAN sport & fitness App, which will provide a large amount of exercises and workouts.



The FSW 214 consist of 4 bars placed at a distance of 175cm. The low bars are 78cm high and the high bars are 118cm high.

ASTM F3101 compliant

Spare parts guaranteed

Sustainability Data

FSW214





Cradle to Gate A1-A3	Total CO ₂ emission	CO₂e/kg	Recycled materials	
	kg CO₂e	kg CO₂e/kg	%	
FSW21400-0900	353.12	3.43	47.96	

The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))

Kompan A/S

C.F. Tietgens Boulevard 32C DK-5220 Odense SØ Denmark



Verification of CO₂ calculation of: Fitness



Data version no. 2023-10-05

The CO_2 calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Fitness" represented by item no.: FAZ10100-0900.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

Date: 30. October 2023 | Valid until: 30. October 2025 Verified by:

mais

Julie Marie Vejsgaard Larsen, LCA & EPD Consultant

Verification based on report: Validation of ${\rm CO_2}$ calculation of 9 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Julie M. V. Larsen.

Publication date: 30. October 2023

By Bureau Veritas HSE
www.bureauveritas.dk
+45 7731 1000




Over Under


FSW214



* Max fall height | ** Total height | *** Safety surfacing area

* Max fall height | ** Total height





Click to see TOP VIEW

Click to see SIDE VIEW