Seesaw with Seats, 4 persons

NRO12201



Item no. NRO12201-0501				
General Product Information				
Dimensions LxWxH	13'7"x0'8"x3'10"			
Age group	5 - 12			
Play capacity (users)	4			
Color options				







The Seesaw 4 is a playground classic. It still attracts players again and again, as it has for generations. The archaic play event is still with us for a reason: the tickling in the stomach when going up high, going down fast is eternally appealing. The Seesaw 4 develops the sense of space and rhythm and leg muscles of children. These are crucial motor skills that help children navigate the world securely, e.g. in the street when estimating time, movement and objects. The social dimension and degree of trust in your peer that is demanded when seesawing, is great training of social-emotional life skills such as turntaking and cooperation. With four users, empathy is trained, too. Players will need to consider others' limits and limitations. Especially in groups of four, the see-sawing is a fantastic social play event.



NRO12201





Rocking movement

Physical: response to movement increases spatial awareness and sense of balance. These are fundamental motor skills that help the child's ability to sit still on a chair which takes a good sense of balance. Cognitive: trains the understanding of cause and effect: when I move my body, the spring responds with movement.





Rocking together Social-Emotional: the possibility of rocking together develops cooperation skills and consideration of others when rocking.



Handhold Physical: the vertical handgrips ensure a firm grip at different heights, necessary for rocking intensely. This trains hand and arm muscles.

Seesaw with Seats, 4 persons



NRO12201



All Organic Robinia products by KOMPAN are made of Robinia wood from sustainable European sources. On request it can be supplied as FSC® Certified (FSC® C004450).



The Robinia wood can be supplied as untreated raw wood or painted with a brown colored transparent pigment that maintains the golden wood color of the wood.



The steel surfaces are hot-dip galvanized inside and outside with lead-free zinc. The galvanization has excellent corrosion resistance in outside environments and requires minimal maintenance.

Item no. NRO12201-0501					
Installation Information					
Max. fall height		3'10"			
Safety surfacing area	2	292ft²			
Total installation time		3.0			
Excavation volume	0.	77yd³			
Concrete volume	C).2yd³			
Footing depth (standard)		2'4"			
Shipment weight	2	75lbs			
Anchoring options	Surface	~			
	In-ground	~			
Warranty Information					
Hot dip galvanized steel	Lif	etime			
Robinia Wood	10 `	Years			
Spare Parts Availability	10 Years				

Elevated activities	Accessible elevated activities	Accessible ground level activities	Accessible ground level play types
Present			
Required			

Sustainability Data

Cradle to Gate A1-A3

NRO12201-0501

NRO12201



Kompan A/S C.F. Tietgens Boulevard 32C DK-5220 Odense SØ Denmark



Verification of CO, calculation of: Nature play



Data version no. 2023-10-05

The CO₂ calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Nature play" represented by item no.: NR0409-0621.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

Date: 30. October 2023 | Valid until: 30. October 2025 Verified by:

mais

Julie Marie Vejsgaard Larsen, LCA & EPD Consultant

Verification based on report: Validation of CO, calculation of 9 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Julie M. V. Larsen.

Publication date: 30. October 2023



www.bureauveritas.dk



The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))

Total CO2

emission

kg CO₂e

75.32

2-1-

CO2e/kg

kg CO₂e/kg

0.66

Recycled

materials

%

34.04



NRO12201

* Max fall height | ** Total height | *** Safety surfacing area

* Max fall height | ** Total height

Click to see TOP VIEW

Click to see SIDE VIEW

