
COR10501






General Product Information

Dimensions LxWxH 415x415x300 cm
Age group 5+
Play capacity (users) 30
Colour options



The Cubite with House Membrane is a threedimensional rope environment that gives children hours of climbing enjoyment. The steel frame is a destination in its own right offering a break or a meeting point. The membranes add a fast, bouncy way to the top and function as destination and meeting points at the same time. Social interaction and stimulation of cooperation is encouraged here. The bouncy ropes and nets of the Cubite add thrills: the child can feel its own and all their friends' movements when using the net. At this height that means risk assessment and concentration. The nets also train important motor skills such as proprioception, spatial awareness and cross-body coordination. These skills are

fundamental for risk assessment when for instance judging and navigating traffic securely.




COR10501







Height Social-Emotional: children develop courage and self-regulation when being up high. This positively affects self-confidence.









Big meshes

Physical: the big meshes allow for climbing and crawling, supporting proprioception, cross coordination and spatial awareness. **Social-Emotional**: allow more children being seated together, sharing.







Connected nets

Physical: the connected nets make the climbers feel the movements of the other climbers. All muscle groups are trained, as well as cross coordination. Social-Emotional: the climbers' movements affect the other climbers, so consideration and turn-taking is supported.







Membrane path

Physical: a faster way up, due to the extra support of the membrane. **Social-Emotional:** a meeting path with points for retreat from the rope landscape.





Transparency

Social-Emotional: the transparency makes cooperation and communication possible, which are essential life skills for children to learn.

COR10501



300 cm




Designed to allow the typical function of rope play structures to move Corocord 'S' clamps are used as universal connections in Corocord products. 8mm stainless steel rods with rounded edges are pressed around the ropes with a special hydraulic press, making them the ideal connector. Our clamps are safe, durable and vandalism-proof.



The aluminium swages of the net are double conical with rounded ends and are as small as safety allows. The overall net design aims at keeping metal parts within the net to an absolute minimum, both in size and number, to provide the best possible rope climbing experience.



Corocord membranes consist of friction-proof rubberised material of conveyor belt quality with excellent UV resistance. Tested and compliant with REACH requirements for PAH. Embedded is a four-layered armouring made of woven polyester. The armouring and the two surface layers result in a total thickness of 7.5 mm.



Safety surfacing area 43.4 m² Total installation time 20.6 Excavation volume 1.76 m³

Item no. COR105011-0412 **Installation Information**

Max. fall height

Rope

Concrete volume 0.98 m³ Footing depth (standard) 110 cm

Shipment weight 766 kg Anchoring options In-ground

Warranty Information Corocord (Hercules) 10 years EcoCore HDPE Lifetime Galvanised Steel Lifetime

Membrane 2 years Spare Parts Guarantee 10 years



The metal parts are made from high-quality steel consisting of hot-dip galvanisation on both the inside and outside and also includes leadfree zinc and an additional layer of powder coating. This ensures both excellent corrosion resistance and colourful design expression.



VENUS

MARS







NEPTUNE

The COROCORD Frame Nets are available in 8 colour themes, ranging from elegant to expressive black or a natural neutral sand colour section to bright eye-catching signal colours which appeals to children of all ages.

TERRA




3 / 08/01/2024 Data is subject to change without prior notice.

Sustainability Data

COR10501





Cradle to Gate A1-A3	Total CO ₂ emission	CO₂e/kg	Recycled materials
	kg CO₂e	kg CO₂e/kg	%
COR105011-0412	1,862.38	3.81	42.81

The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))

Kompan A/S

C.F. Tietgens Boulevard 32C DK-5220 Odense SØ Denmark



Verification of CO₂ calculation of: Corocord



Data version no. 2023-10-05

The CO_2 calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Corocord" represented by item no.: $\mathrm{COR314011}$ -1101.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

Date: 30. October 2023 | Valid until: 30. October 2025 Verified by:

mase

Julie Marie Vejsgaard Larsen, LCA & EPD Consultant

Verification based on report: Validation of CO_2 calculation of 9 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Julie M. V. Larsen.

Publication date: 30. October 2023


By Bureau Veritas HSE
www.bureauveritas.dk
+45 7731 1000


COR10501



* Max fall height | ** Total height | *** Safety surfacing area

* Max fall height | ** Total height





Click to see TOP VIEW

Click to see SIDE VIEW