
# Mega Deck

PCM100931



Item no. PCM100931-0951				
General Product Information				
Dimensions LxWxH	472x448x321 cm			
Age group	2+			
Play capacity (users)	14			
Color options				







This fantastic play tower will inspire young children to play actively, using their muscles to climb to the top and slide to the ground. The variety of access points provide graded, ageappropriate challenges. They strengthen muscles and help develop cross-coordination skills. Cross-coordination skills enhance children's abilities to use both sides of their

brain and supports the internal structures that enable reading and thinking. The desk at ground level extends the play space and attracts children to meet, stay, and play. The double slide is a great team play feature. Sliding supports posture and balance, fundamental motor skills for the child feeling secure in its movements.

14



PCM100931





Pipe ladder Physical: cross coordination and eye-hand coordination are supported when children climb the ladder. The climbing also supports leg and arm muscles. Social-Emotional: learning about turn taking and cooperation.





### Window Social-Emotional: invites interaction between sides and cooperative play.



# Desk

**Social-Emotional:** fine meeting place and a space creator. Sharing and cooperation from both sides create a social scenario that supports communication and cooperation.



## Double slide

Physical: sliding develops spatial awareness and a sense of balance. Furthermore, the core muscles are trained when sitting upright going down. Social-Emotional: invites socializing, supports parent-child and peer-to-peer play. Cognitive: young children train their understanding of space, speed and distances when sliding down quickly.



#### Rock climber Physical: supports cross

Physical: supports cross coordination and leg, arm and hand strength. Social-Emotional: the inclination makes climbing feel secure, especially for younger children.

# Mega Deck

PCM100931





Panels of 19mm EcoCore<sup>™</sup>. EcoCore<sup>™</sup> is a highly durable, eco friendly material, which is not only recyclable after use, but also consists of material produced from +95% recycled post consumer material from food packing waste.



Main posts with hot dip galvanized steel footing are available in different materials: Pressure impregnated pine wood posts. Pre-galvanized inside and outside with powder coated top finish steel posts. Lead free aluminum with color anodized top finish. Greenline TexMade posts of 95% post-consumer recycled PE and textile waste.



All decks are supported by unique designed low-carbon aluminum profiles with multiple attachment options. The grey colored molded decks are made of 75% post-consumer waste PP material with a non-skid pattern and texture surface.

Item no. PCM100931-0951				
Installation Information				
Max. fall height	100	) cm		
Safety surfacing area	37.	3 m²		
Total installation time	16.5 h	ours		
Excavation volume	0.7	9 m³		
Concrete volume	0.0	0 m³		
Footing depth (standard)	90	) cm		
Shipment weight	52	5 kg		
Anchoring options	Surface	~		
	In-ground	~		
Warranty Information				
EcoCore HDPE	Life	time		
Post	10 y	ears		
PP Decks	10 y	ears		
Spare parts guaranteed	10 y	ears		



The steel surfaces are hot dip galvanised inside and outside with lead free zinc. The galvanisation has excellent corrosion resistance in outside environments and requires low maintenance.

The slides can be chosen in six different colors and three materials: Straight or curved onepiece molded PE slides, made from 33% recycled post-consumer materials in different colours. Combined EcoCore™ sides and stainless-steel. Full stainless steel in one piece design for more vandalism proof solutions.



Wood version of FSC®-certified (FSC®C004450) pine wood with pressure impregnated base treatment and brown painted top finish. Vertical boards and top ends protected by a unique aluminum profile for high outdoor durability.



# **Sustainability Data**

PCM100931




C	radle to Gate A1-A3	Total CO₂ emission	CO₂e/kg	Recycled materials
		kg CO₂e	kg CO₂e/kg	%
	PCM100931-0951	826.46	1.97	58.88
	PCM100931-0901	881.20	2.26	53.03

The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))



Kompan A/S C.F. Tietgens Boulevard 32C DK-5220 Odense SØ Denmark







### Data version no. 2023-10-05

The  $CO_2$  calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Play systems" represented by item no.: PCM200321-0950.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

Date: 30. October 2023 | Valid until: 30. October 2025 Verified by:

mais

Julie Marie Vejsgaard Larsen, LCA & EPD Consultant

Verification based on report: Validation of CO<sub>2</sub> calculation of 9 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Julie M. V. Larsen.

Publication date: 30. October 2023



Data is subject to change without prior notice.



PCM100931

\* Max fall height | \*\* Total height | \*\*\* Safety surfacing area

\* Max fall height | \*\* Total height

