



Langur Trail

CRP251901

Item no. CRP251901-0901

General Product Information

Dimensions LxWxH	2172x743x307 cm
Age group	6+
Play capacity (users)	47
Color options	



The Langur Trail with its linear layout provides highly attractive challenges for children, again and again. Lots of varied, responsive, swaying and bouncing nets and ropes take concentrated movement to cross, adjusting for different grips and rhythms of climbing. This trains agility, balance and coordination skills. These motor skills are fundamental for body

confidence and eventually concentrating and sitting still on a chair. Apart from being great fun, the Horizontal nets, the Cube net and Shaky Pods allow children to take a break and socialize or cooperate when combining breaks and movement through the structure. This develops important social-emotional skills such as turn-taking, empathy and self-regulation.

The bouncy, swaying range of challenging play makes the Langur Trail a highly attractive play unit that supports children's development through fun play.

Langur Trail

CRP251901



Ropes of UV-stabilized PES rope strands with inner steel cable reinforcement. The polyester yarn is made from +95% post-consumer materials and is inductively melted onto each strand.




Corocord 'S' clamps are used as universal connections in Corocord products. 8mm stainless steel rods with rounded edges are pressed around the ropes with a special hydraulic press, making them the ideal connector: safe, durable and vandalism-proof, all while allowing the typical movement of rope play structures.



Corocord smart clamps are carefully designed in every detail to ensure superior flexibility in high quality aluminum material. The smart clamps are attached around the posts with four steel bolts. Not used attachment points are closed with PA caps.


Item no. CRP251901-0901	
Installation Information	
Max. fall height	290 cm
Safety surfacing area	147.3 m ²
Total installation time	37.2
Excavation volume	24.61 m ³
Concrete volume	13.67 m ³
Footing depth (standard)	90 cm
Shipment weight	1,766 kg
Anchoring options	Surface ✓ In-ground ✓



Decorative elements (fish-shaped) are made of stainless steel.



Panels of 19mm EcoCore™. EcoCore™ is a highly durable, eco friendly material, which is not only recyclable after use, but also consists of material produced from +95% recycled post consumer material from food packing waste.




Balance pads are made of EPDM rubber. Material is UV stabilised.



Sustainability Data

CRP251901




Cradle to Gate A1-A3	Total CO ₂ emission	CO ₂ e/kg	Recycled materials
	kg CO ₂ e	kg CO ₂ e/kg	%
CRP251901-0901	4,068.20	3.57	44.90

The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))

Kompan A/S
 C.F. Tietgens Boulevard 32C
 DK-5220 Odense SØ
 Denmark



Verification of CO₂ calculation of: Corocord



Data version no. 2023-10-05

The CO₂ calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Corocord" represented by item no.: COR314011-1101.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

Date: 30. October 2023 | Valid until: 30. October 2025

Verified by:

Julie Marie Vejsgaard Larsen, LCA & EPD Consultant

Verification based on report: Validation of CO₂ calculation of 9 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Julie M. V. Larsen.

Publication date: 30. October 2023

By Bureau Veritas HSE
 www.bureauveritas.dk
 +45 7731 1000





Langur Trail

CRP251901

* Max fall height | ** Total height | *** Safety surfacing area

* Max fall height | ** Total height



[Click to see TOP VIEW](#)

[Click to see SIDE VIEW](#)